

MW-9 2311026

1 LOCATION OF WATER WELL:
County: HARVEY

Fraction
SW 1/4 SW 1/4 SW 1/4


Section Number
33

Township Number
T 24 S

Range Number
R 1 E/W

Distance and direction from nearest town or city street address of well if located within city?
~~324 EAST 425th STREET, SEDGEMAN, KS 67447~~ SN 125th STREET NORTH AND OLD HIGHWAY 81 INTERSECTION

2 WATER WELL OWNER: KDHE
RR#, St. Address, Box #: FORBES FIELD BUILDING 740
City, State, ZIP Code: TOPEKA, KS 66620
Board of Agriculture, Division of Water Resources
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:


4 DEPTH OF COMPLETED WELL: 20.5 ft. ELEVATION:
Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL 19.80 ft. below land surface measured on mo/day/yr 8-11-95
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 8 in. to ft. and in. to ft.
WELL WATER TO BE USED AS:
5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No + If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes No +

5 TYPE OF BLANK CASING USED:
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
Blank casing diameter 2 in. to ft. Dia in. to ft. Dia in. to ft. Dia in. to ft. Dia in. to ft. Dia in. to ft.
Casing height above land surface FLUSH in. weight 703 lbs./ft. Wall thickness or gauge No. 154
TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)
7 Torch cut
SCREEN-PERFORATED INTERVALS: From 14 ft. to 24 ft. From ft. to ft. From ft. to ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 12 ft. to 24 ft. From ft. to ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 12 ft. to 1.5 ft. From ft. to ft. From ft. to ft. From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
13 Insecticide storage
Direction from well? NORTH NORTHWEST How many feet? 150 AND 220

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2.5	SILT, SAND			
2.5	11.0	CLAY, SAND			
11.0	14.0	SILT, CLAYEY			
14.0	24.0	SAND,			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-11-95 and this record is true to the best of my knowledge and belief. Kansas
Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 8-16-95
under the business name of GST by (signature) Steve Nudler