						WWC-5 KSA 82a-1212					
		TER WELL:	Fraction	1/4 NW1/4	1/11	Section, Number	1	ip Number	١ ,٠	Number	
County:	Harv	Yom poorest tour	· NW	address of well if to	reated within	ih/2	T	7 s	I R	EM	
		• • • • •		,	ocated within c	rty ?				1	
		4 196,	Neu								
2 WATER	R WELL OW	NER: Paul	Howard	ILV							
RR#, St.	Address, Bo	×# 242	New		L			l of Agriculture, (Division of Wa	ater Resources	
				cs 67219)	Application Number: ft. ELEVATION: 1420.95				
J LOCATI	E WELL'S L IN SECTION										
		1	epth(s) Groun	ndwater Encountere	d J	7	2	ft. 3		ft.	
Ĭ I	v !	! [[v	VELL'S STAT	IC WATER LEVEL		ft. below land su	rface measure	ed on mo/day/yr	10-16	7.7.2	
	- NW	NE	Pur	mp test data: Well	water was	$A \cdots ft. a$	after	hours pu	mping	gpm	
1	1										
l≞ w L	1	F B	Bore Hole Diar	meter % ir	n. to /.7 •	. 5			to		
<u>×</u> ×	!	! ⁻ v	VELL WATER	TO BE USED AS:		water supply	8 Air condition	Ū	Injection well		
ī L	_ sw	SE	1 Domesti	c 3 Feedlot		water supply			Other (Specif		
	1	;	2 Irrigation			and garden only					
l↓ L	ı	1 1	Vas a chemica	al/bacteriological san	nple submitted	to Department? Y	esNo	,X; If yes,	_		
-		n	nitted			Wa	ater Well Disin	fected? Yes	(No)		
5 TYPE (OF BLANK (CASING USED:		5 Wrought iron	8 C	oncrete tile	CASING	G JOINTS: Glued	i Cla	mped	
1 Ste		3 RMP (SR)		6 Asbestos-Cen	nent 9 O	ther (specify below	w)	Weld	ed		
Ø₽V	/C	4 ABS	2	7 Fiberglass				Threa	aded		
Blank casi	ng diameter	ir	. جے 1. to	ft., Dia	ir	n. to	ft., Dia .		in. to	ft. [
Casing he	ight above la	and surface	29.5	in., weight	<i></i>	Ibs	ft. Wall thickn	ess or gauge N	o 4.0 .		
TYPE OF	SCREEN O	R PERFORATION	MATERIAL:		\mathcal{C}	∵ Pvc	10	Asbestos-ceme	ent		
1 Ste	eel	3 Stainless	steel	5 Fiberglass	8	RMP (SR)	11	Other (specify)		<i></i>	
2 Bra	ass	4 Galvanized	d steel	6 Concrete tile	9	ABS	12	None used (op	en hole)		
SCREEN	OR PERFO	RATION OPENING	S ARE:	5 (Gauzed wrappe	ed	8 Saw cut		11 None (o	pen hole)	
1 Co	ntinuous slo	ot 3 Mill	slot	6 \	Wire wrapped		9 Drilled he	oles			
2 Lo	uvered shut	ter 4 Key	punched	7	Forch cut	_	10 Other (sp	pecify)			
SCREEN-I	PERFORATI	ED INTERVALS:	From	ft.	to	3 ft., Fro	m	ft. t	0		
			From		to	, 👆 ft., Fro	m	ft. t	o <i></i>		
	RAVEL PA	CK INTERVALS:	From	1.5 ft.	to	ج ft., Fro	m	ft. t	0		
			From	ft.		ft., Fro		ft. to		ft.	
6 GROUT	MATERIAL	.: 1 Neat ce		2 Cement grout	(3)						
Grout Inter	vals: From	m ft	. to <i>O</i>	.5. ft., From .	0.5	ft. to	ft., Fro	m	ft. to		
What is th	e nearest so	ource of possible co	ontamination:			10 Lives	stock pens	14 A	bandoned wa	iter well	
1 Septic tank 4 Lateral lii						11 Tuel storage		15 Oil well/Gas well			
2 Sewer lines 5 Cess poo			ool	8 Sewage lagoon			lizer storage	16 O	16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							-				
Direction f	•	NW	•	,				500		i	
FROM	ТО	/	LITHOLOGIC	CLOG	FRO			PLUGGING II	NTERVALS		
0	3.5	Silter	Clay								
3.5	815	Silt									
8,5	/3	5, It	with	Clay							
13	14.5	Sana	/								
1>	1,1			***************************************							
										1	
			S CERTIFICA	TION: This water w	ell was (1) cor						
1	on (mo/day	,	3-95					ne best of my kno	owledge and	belief. Kansas	
		s License No	.5.71	This Wa	ter Well Record	d was completed	on (mo/day/yr	1 13	760		
under the	business na	me of $\mathcal{B}\mathcal{D}\mathcal{F}$	ł7			by (signa	iture)	2 Ill	uf-		
				FIRMLY and PRINT clea 620-0001. Telephone: 913						Department	