				H WELL RECO	RD Form	NWC-5	KSA 82a-						
	ON OF WAT	ER WELL:	Fraction		ar.		on Number	1	hip Number	•	Range Nu	ımber	
County:			SW 1/4		SW 1/2		7	T	24 <sub>S</sub>	<u> </u>	R IE	E/W	
Distance a	nd direction	from nearest town	or city street a	address of well if	located within	city?							
5600	S. Mer:	idian New	ton, Kansa	as									
2 WATER	R WELL OW	NER: Schroe	eder,Lorer	1									
<b>.</b> RR#. St. <i>F</i>	Address, Box	# : 316 Cc	nesotga I	Orive				Board	d of Agricult	ure, Divis	sion of Water	r Resources	
	ZIP Code		,Kansas					Appli	cation Numb	ber:			
		OCATION WITH 4			80	)	# FLEX/A3						
AN "X"	IN SECTION	1 DOV											
	<u> </u>			water Encounte									
Ŧ I	-	!     W		WATER LEVE									
I L	- NW	NE	Pum	p test data: We	ell water was		ft. af	ter	hour	rs pumpi	ng	gpm	
ÌΓ	-	-     E	st. Yield	gpm: We	ell water was		ft. af	ter	hour	rs pumpi	ng	gpm	
<u>.</u>	_ i _ [	I B	ore Hole Diam	eter11	.in. to	. , <u>8</u> 0.	ft., a	ınd		in. to			
* w  -	1	ı w	ELL WATER	TO BE USED AS	S: 5 Pub	ic water	supply	8 Air conditi	oning	11 Inje	ction well		
- k		1	1 Domestic	3 Feedlo	t 6 Oil f	ield wate	r supply	9 Dewaterin	ıq	12 Oth	er (Specify b	pelow)	
P	- SW	SE	2 Irrigation	-			rden only 1		-				
1 1	- !	!	•	bacteriological s		-	-						
į L				bacteriological s	ample submitt	su to Dep		er Well Disi				DIE Was sub	
			itted										
		ASING USED:		5 Wrought iro			e tile				C Clamp		
1 Ste		3 RMP (SR)		6 Asbestos-Co		•	specify below	•					
2 PV	_	4 ABS	_	7 Fiberglass			?–26				<b>1</b>		
		in											
Casing hei	ght above la	and surface	.12	.in., weight	2.29		lbs./f	t. Wall thick	ness or gau	ge No	214	: <i></i>	
TYPE OF	SCREEN OF	R PERFORATION I	MATERIAL:			7 PVC		10	0 Asbestos-	cement			
1 Ste	eel	3 Stainless s				8 RMP (SR)			11 Other (specify)				
2 Bra	ass	4 Galvanized				9 ABS			12 None used (open hole)				
		RATION OPENINGS								11 None (open hole)			
	ntinuous slo				Wire wrappe	•		9 Drilled h			толо (орол	,	
		-	punched		Torch cut	u							
	uvered shutt	·	•	23 1		90							
SCHEEN-	PERFORATE	ED INTERVALS:					•						
					ft. to								
G	BRAVEL PAG	CK INTERVALS:	From	22 1		80.							
			From		t. to		ft., Fron			ft. to		ft.	
6 GROUT	MATERIAL	: 1 Neat cer	ment	2 Cement grou	t 3	Benton	ite 4	Other					
Grout Inter	vals: From	n ft.	. to	4 ft., From	<del></del>	ft. to	) <i></i> .	ft., Fro	om		ft. to	ft.	
What is the	e nearest so	urce of possible co	ontamination:				10 Livest	ock pens		14 Aban	doned water	well	
1 Septic tank 4 Lateral lin			lines				11 Fuel storage			15 Oil well/Gas well			
2 Sewer lines 5 Cess poo										16 Other (specify below)			
3 Watertight sewer lines 6 Seepage						13 Insecticide storage				None Apparent			
Direction f	•	ci iiilos o ocopag	,o p.,	0 1 000	yara		How man	•	21011	cppc	ar Circ		
FROM	TO TO		LITHOLOGIC	LOG	l Fi	ROM	TO	ly leet?	PLUGGI	NG INTE	RVALS		
0	3	topso	il	LOG		TOW!	'0						
3	11	clay				+	<del>-</del>						
11	27	fine s	gand										
27	80	grey				+							
	80	grey s	Silate										
										Andrew Control of the			
7 CONTE	RACTOR'S (	DR LANDOWNER'S	S CERTIFICAT	TION: This water	well was (1)								
completed	on (mo/day/	year) 9-30-9	91				and this reco	rd is true to t	the best of r	ny knowl	edge and be	ljef. Kansas	
completed	on (mo/day/	0 20 (	91				and this reco	rd is true to to on (mo/day/y	the best of r	ny knowl		lief. Kansas	