L commonwers	T ND A CENTON	Water Well Record	Form WWC-5	KSA 82a-1212			
1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number	
Harvey	SE 1/4	SW 1/4 SE	1/4	34	т 24 s	R 1E E/W	
Distance and direction frem nearest town or o	-	•					
I-35 and 125th		<u> East Hillsi</u>	<u>de</u>	Sedgwid	k, Kansas		
	UM, Jerry						
	2 E. 125th				Board of Agriculture,	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Sec	lqwick, Kans				Application Num	per:	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		IPLETED WELL	55	ft. ELE	VATION:		
AN A INSECTION BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
	WELL'S STATIC W	ATER LEVEL 3	FT. E	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	10/20/1998	
NWNE	Pump test	data: Well wat	er was	ft. a	fter hours pu	mping gpm	
	Est. Yield	gpm: Well wat	er was	ft. a	ifter hours pu	mping gpm	
W F	Bore Hole Diameter	12 in. to	55	ft.	and in	to ft.	
T	WELL WATER TO		ublic water s	supply 8	•	Injection well	
swse	1 Domestic		Oil field wate		Dewatering 12	Other (Specify below)	
	2 Irrigation		awn and gai) Monitoring well		
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		riological sample subm	itted to Dep			mo/day/yr sample was	
	submitted			Wate	r Well Disinfected? Yes	X No	
5 TYPE OF CASING USED:		5 Wrought iron		Concrete tile		Glued X Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement	90	ther (Specify be	low)	Welded	
2 PVC 4 ABS		7 Fiberglass	SD	R-26		Threaded	
Blank casing Diameter 5	in. to 27	ft., Dia	in.	to	ft., Dia in.	to ft.	
	12 in.,	weight 2.3			Vall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORA		f Fibereless		PVC	10 Asbestos-cer		
1 Steel 3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (speci	• •	
2 Brass 4 Galvanized st	eel	6 Concrete tile	9 A	ABS	12 None used (pen hole)	
SCREEN OR PERFORATION OF		5 Gauzed			8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key	punched	7 Torch cu	ıt		10 Other (specify)		
SCREEN-PERFORATION INTER	VALS: from 27	ft. to	55	ft., From	ft. to	ft.	
	from	ft. to		ft., From	ft. to	ft.	
GRAVEL PACK INTER	RVALS: from 24	ft. to	55	ft., From	ft. to	ft.	
	from	ft. to		ft., From	ft. to	ft.	
O one or warrante	t cement 2 C	ement grout	3 Bente	onite	4 Other		
Grout Intervals: From 4	ft. to 24	ft. From	ft. to	•	ft. From	ft. to ft.	
What is the nearest source of possible contamination:				10 Livestoc	• 44	Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel sto	13	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilize		16 Other (specify below)	
3 Watertight sewer lines 6 See	page pit	9 Feedyard		13 Insectic	nde storage Non	e Apparent	
Direction from well?					How many feet?		
FROM TO	LITHOLOGIC LOG		FROM	ТО	PLUGGING INT	ERVALS	
0 15 fine sa				-			
15 25 clay sa:							
25 52 fine sa	na						
52 55 shale							
							
 							
							
 							
			-9				
				 			
<u> </u>					A		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No236							
Under the business name of AALDNELL							
	arb…werr…#…	rump servic	etno	Z by (signa	ture) 7/_/	l H	