

1 LOCATION OF WATER WELL: Harvey	FRACTION NW 1/4 NW 1/4 NW 1/4	Section Number 8	Township Number T 24 S	Range Number R 1E E/W
--	---	----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
From Halstead, KS. 1 m. S., 2 m. E., approx 100ft S. on S. side of road

WATER WELL OWNER: BECKER, Melvin	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 207 Locust	Application Number:
CITY, STATE, ZIP CODE: Halstead, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 03/02/1999 Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 12 in. to 80 ft. and in. to ft.	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <input checked="" type="checkbox"/> No	

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS	5 Wrought iron 6 Asbestos-Cement 7 Fiberglass	8 Concrete tile 9 Other (Specify below) SDR-26	CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped Welded Threaded
Blank casing Diameter 5 in. to 60 ft., Dia in. to ft., Dia in. to ft.	Casing height above land surface 12 in., weight 2.35 lbs./ft.	Wall thickness or gauge No. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 2 Brass 4 Galvanized steel	5 Fiberglass 6 Concrete tile	8 RMP (SR) 9 ABS	11 other (specify) 12 None used (open hole)
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 2 Louvered shutter 4 Key punched	5 Gauzed wrapped 6 Wire wrapped 7 Torch cut	8 Saw cut 9 Drilled holes 10 Other (specify)	11 None (open hole)
SCREEN-PERFORATION INTERVALS: from 60 ft. to 80 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: from 24 ft. to 80 ft., From ft. to ft.			

6 GROUT MATERIAL: 1 Neat cement Grout Intervals: From 4 ft. to 24 ft. From ft. to ft.	2 Cement grout	3 Bentonite	4 Other bentonite hole plug
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit	7 Pit privy 8 Sewage lagoon 9 Feedyard	10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage	14 Abandon water well 15 Oil well/Gas well 16 Other (specify below)
Direction from well? West How many feet? 20			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	topsoil			
4	58	clay			
58	80	medium sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/02/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 . This Water Well Record was completed on (mo/day/yr) 03/03/99 . Under the business name of Harp Well & Pump Service, Inc. by (signature) <div style="text-align: right;"><i>Todd S. Harp</i></div>
--