1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	d Form WWC-5	KSA 82a-1212 Section Number	Township Number	Dowgo Number	
<u> </u>		SE 1/4 S	SE 1/4	34	Township Number	Range Number	
Harvey Distance and direction frem nearest town or city stre			OE 1/4	34	T 24 s	R 1E E/W	
1/4 North of 125th N. Sedgwick, Kansas							
WATER WELL OWNER: WINTER, Wayne							
	S. Hills:	ice			Board of Agriculture,	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Sedaw:				Application Number:			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COM	PLETED WELL	60		EVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundwa	ter Encountered	1	ft.	2 ft.	3 ft.	
	ELL'S STATIC WA	<u>- </u>	•	. BELOW LAND SU	JRFACE MEASURED ON mo/day/yr	08/17/1999	
NWNE	Pump test		water was	ft.	after hours pu		
Est.	Yield	- ·	water was	ft.	after hours pu		
	e Hole Diameter LL WATER TO B	12 in.	to 60 5 Public wate	ft.	and in. 8 Air conditioning 11	. to ft. Injection well	
	1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)	
sw sw s	2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring well	Canal (officer)	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was						mo/day/yr sample was	
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Ceme	ent 9	Other (Specify		Welded	
2 PVC 4 ABS		7 Fiberglass	S	DR-26		Threaded	
Blank casing Diameter 5 in.	to 30	ft. , Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 12	in.,	weight 2		lbs. / ft.	Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATIO	N MATERIAL:	5 Fiberglass		7 PVC 8 RMP (SR)	10 Asbestos-cei		
1 Steel 3 Stainless Steel		6 Concrete tile		, ,	11 other (speci	**	
2 Brass 4 Galvanized steel				9 ABS	12 None used (8 Saw cut	* ′	
S Gallet Wild ARE.						11 None (open note)	
The state of the s							
/ Interest							
SCREEN-PERFORATION INTERVALS	50		. to 60	ft., From		_	
from GRAVEL PACK INTERVALS: from 26			t. to t. to 60	ft., Fro ft., Fro			
GRAVELTACK INTERVAL	from		t. to	ft., Fro	=== -		
6 GROUT MATERIAL: 1 Neat cem	•	ement grout		ntonite		e hole plug	
Grout Intervals: From 4 ft	. to 24	ft. From	ft.	to	ft. From 24	ft. to 26 ft.	
What is the nearest source of possible contamination:				10 Livest	ock pens 14	Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel s		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon				16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? West	HOLOGIC LOC		EDOM	1 mo 1	How many feet? 200		
	HOLOGIC LOG		FROM	TO	PLUGGING INT	ERVALS	
0 3 topsoil 3 6 clay 6 11 sandy clay							
6 11 sandy clay	7						
11 27 fine silty				1			
27 39 fine to me		1					
39 43 clay							
43 44 fine sand						·····	
44 60 grey shale	9						
							
				<u> </u>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No2	36	This Water Well	Record was	completed on (mo/day/yr)Q8/	20/99	
Under the business name of HarpWell							
					Iodd	S. Harp	