<u> </u>					Water Well R	ecord Form WWC				
1 Loca	_	ATER WELL:	. 1	FRACTION SE	SE SE NI	N	Section Number	Township Number	Range Number	
└		RUEY	<u> </u>	SÆ 1/4	NE 1/4	MW 1/4	39 16	т 265 в 24	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?										
3/4 m. N. of SW 72nd & 1/2 E. of S. Kansas Rd.										
	TER WELL	OWNER: PIN	AIRE	I, Zeke						
RR#,	ST. ADRESS	BOX#: 200	s.	Ridge				Board of Agriculture,	Divivsion of Water Resource	
CIT	, STATE, ZII			. Kansa	18			Application Numb	er:	
		LOCATION WITH	4 D	EPTH OF CO	MPLETED WEL	т 80	ft. ELE	VATION:		
AN "X	" IN SECTIO	N BOX:	☐ De	pth(s) groundw	ater Encountere	d 1	ft.	2 ft.	3 ft.	
WELL'S STATIC WATER						20 F	T. BELOW LAND SUR	FACE MEASURED ON mo/day/yr	09/14/2000	
	NW	X NE		Pump tes	t data: We	ell water was	ft. a	fter hours pun		
1	,,,,,		Est. Y	'ield	gpm: W	ell water was	ft.	after hours pur		
1 Mile	/	H-	Bore I	Hole Diameter	12 in.	to 80	ft.	and in.	to ft.	
= ``			WELI	WATER TO	BE USED AS:	5 Public wat	er supply (Air conditioning 11	Injection well	
1 .			1	Domestic	3 Feedlot	6 Oil field w	ater supply	Dewatering 12	Other (Specify below)	
2 Irrigation 4 Industrial 7 Lawn at							l garden only 10 Monitoring well			
			Was a	chemical/bact	eriological sampl	e submitted to I	epartment? Yes	No X ; If yes, 1	no/day/yr sample was	
<u> </u>		S		nitted				er Well Disinfected? Yes	X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped										
1 Stee	el	3 RMP (SR)			6 Asbestos-Ce	ement	Other (Specify be		Velded	
2 PV	2	4 ABS			7 Fiberglass	9	DR-26	•	Threaded	
Blank c	asing Diam	eter 5	in.	to 25	ft., Dia	in		ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214										
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement										
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)										
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									pen hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11									11 None (open hole)	
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes										
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)										
SCREEN-PERFORATION INTERVALS: from 25 ft. to 80 ft., From ft. to ft.										
				from		ft. to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24					ft. to 80		ft., From	ft. to	ft.	
				from		ft. to	ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug										
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.										
What is the nearest source of possible contamination:							10 Livestock pens 14 Abandon water well			
1 Septic tank 4 Lateral lines					7 Pit pr i v	у	11 Fuel sto	13	Oil well/Gas well	
2 Sewer lines 5 Cess pool					8 Sewage l	agoon	12 Fertiliza	er storage 16 (16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent									Apparent	
Direction from well? How many feet?										
FROM	TO		LITHO	LOGIC LOG		FROM	TO	PLUGGING INTE	RVALS	
0	3	topsoil								
3	15	clay								
15	18	fine sar								
18	80	grey sha	ale							
										
			-							
									ALAP AND	
—										
7 CO	NTRACTO	R'S OR LANDOWNE	ER'S CER	TIFICATION: Th	is water well wa	ıs (1) construc	ted, (2) reconstru	cted, or (3) plugged under i	ny jurisdiction and	
was c	ompleted	on (mo/day/yeaı	r)	09/14/	0.0	and this re	cord is true to the	best of my knowledge and	belief. Kansas Water	
								/day/yr)09/1	5/00	
Under the business name of Harp Well & Pump Service. Inc. by (signature)										
i	Todd S. Harp									