


1 LOCATION OF WATER WELL: County: <u>Harvey</u>		Fraction <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	Section Number <u>33</u>	Township Number T <u>24</u> S	Range Number R <u>1</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city? <u>125th & Broadway, Sedgwick, KS.</u>					
2 WATER WELL OWNER: <u>Don Franz</u> RR#, St. Address, Box #: <u>125th & Broadway</u> City, State, ZIP Code: <u>Sedgwick, Ks.</u> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: <u>25'</u> ft. ELEVATION: Depth(s) Groundwater Encountered <u>1.20'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>19.95'</u> ft. below land surface measured on mo/day/yr <u>1-25-96</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>8 1/2"</u> in. to <u>25'</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well <u>Air Sparge Ob. Well</u> Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <u>2 PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>2.375</u> in. to <u>10'</u> ft., Dia. in. to ft., Dia. in. to <u>SDR 13</u> ft. Casing height above land surface <u>FLUSH ML</u> in., weight lbs./ft. Wall thickness or gauge No. <u>SCH 40</u> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <u>25'</u> ft. to <u>10'</u> ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>25'</u> ft. to <u>8'</u> ft., From ft. to ft. From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: Grout Intervals: From <u>8'</u> ft. to <u>4'</u> ft., From <u>4'</u> ft. to <u>0'</u> ft., From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage <u>Father</u> 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>East</u> How many feet? <u>10'</u>					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.50	Asphalt			
.50	2.75	Dk brn gray/brn clay, firm, no odor, dry to moist, low plasticity.			
2.75	12	Red brn clay to sand clay, tight, moist to dry, no odor.			
12	22.25	Gray-red brn mottled silty sandy clay w/ green gray clay mottling, moist, faint odor, firm, some fine-coarse grained sand.			
22.25	25	Lt tan-white fine grained sand, wet, strong odor.			
		Hard-caliche/weathered limestone.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>1-25-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>2-11-96</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Bieker</u>					