	WATER WELL RECORD FO	orm WWC-5 K	SA 82a-1212		
1 LOCATION OF WATE		SECTION NUMBER		RANGE NUMBER	
Harvey	SW 1/4 SW 1/4 SW	1/4 33	T 24 S	R 1E E/W	
Distance and direction from nearest town or city street address of well if located within city?					
1/2 mile North of 125th St. N. & 150' East of Broadway on Hwy. 81  Newton, Kansas  BUILDERS CONCRETE SUPPLY					
RR#,ST. ADDRESS	- 1 1 1 - 1		Board of Agr	iculture, Division of Water Resource	
1	STATE: Newton, Kansas	ZIP CODE:	Application Nur	nber:	
3 LOCATE WELL'S LO	1.1		ELEVATION:		
WITH AN "X" IN SEC	Depth of groundwater Encountered:	ft.	ft.	ft.	
lı <del>-                                   </del>	WELL'S STATIC WATER LEVEL 20	FT. BELOW LAND SU	IRFACE MEASURED ON mo/o	day/yr: 3/6/07	
MW	Pump test data: Well water			s of pumping @ gpm	
1 1	Est. Yield: gpm Well water		ft. after hours	s of pumping @ gpm	
w <u>S</u> w	Bore Hole Diameter 12 in.	to 105 ft.	and in.	to ft.	
_	WELL WATER TO BE USED AS:		9. Dewateri	ng 11. Injection well	
SW		er supply 7. Lawn a		12. Other (Specify below)	
X	2. Irrigation 4. Industrial 6. Oil field wa Was a chemical/bacteriological sample submitted to D	ater supply 8. Air con epartment? YES		what mo/day/yr was sample	
S	submitted		Vater Well Disinfected?	YES NO	
5 TYPE OF CAS	SING USED: 5. Wrought Iron 7. Fiberglass	9. Other (Specify	below) CASING JOINTS:	Glued Threaded	
1. Steel 3. RPM (SR) Welded Clamped					
2. PVC	4. ABS 6. Asbestos-Cement 8. Concrete till	e			
Blank casing diamet		in. to	ft., Dia.	in. to ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214					
TYPE OF SCREEN OR PERFORATION MATERIAL:  1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)					
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)  2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)					
The state of the s					
1. Continuous slo	DRATION OPENINGS ARE:  3. Mill slot 5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None ( open hole)	
				,	
2. Louvered shutte		8. Saw cut	10. Other (specify)		
SCREEN - PERFORA	ATION INTERVAL From 25 ft. to	105 ft.,	From ft.	to ft.	
	From ft. to	ft.,	From ft.	to ft.	
GRAVEL PA	CK INTERVALS: From 24 ft. to	105 ft.,	From ft.	to ft.	
	From ft. to	ft.,	From ft.	to ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug					
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From 35 ft. to 40 ft.					
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy  10. Livestock pens  13. Insecticide storage  15. Oil well/Gas well					
S Squage larges 11 Final storage 14 Abandan undan und 16. Other (specify bel					
None Apparent					
3. Watertight sewer Direction from well?	Frine 0. Seepage pit	<b>.</b> .	How many feet?		
From To	LITHOLOGIC LOG	From To	LITHOLO	OGIC LOG	
0 4	topsoil				
4 15	clay				
15 34	medium sand				
34 105	shale and limestone				
<u> </u>					
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and					
was completed on (mo/day/year) 3-8-2007 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3-9-2007					
under the business	under the business name of Harp Well and Pump Service by (signature)  Todd S. Harp				
10003. TOUP					