	WATER WELL RE	ECORD F	orm WW	/C-5 K	SA 82a-1212	2			
1 LOCATION OF WATER WELL:	l			SECTION NUMBER TOWNSHIP N					
Harvey	SE 1/4 SE	1/4 SE	1/4	27	⊤ 24	S	R 11	E/W	
Distance and direction from nearest town or city street address of well if located within city? 1 1/4 mile North of 125th St. N., East side of Spencer Rd. Sedgwick, Kansas									
2 WATER WELL OWNER: LITSEY, Clint									
	SS,BOX #: 9729 S. Spencer Board of Agriculture, Division of Wate							/ater Resource	
CITY, STATE: Wic	hita, Kansas			P CODE:	-	Application Num	nber:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED W	VELL: 50	ft.		ELEVATION:				
	epth of groundwater Encounte		ft.			ft.		ft.	
	VELL'S STATIC WATER LEV			W LAND SU	RFACE MEASUR	ED ON mo/d	lay/yr: 10/3	0/07	
NW NE								gpm	
W W E E	Est. Yield: gpm Bore Hole Diameter 12	Well wate 2 in.	erwas to 5	6 0 ft.	ft. after and		of pumping @ to	gpm ft.	
	VELL WATER TO BE USED		10 5		and	in. 9. Dewateri r	44 1-1-	ction well	
- SW SE 1									
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? VFS (NO); if yes, what mo/day/yr was sample									
	Was a chemical/bacteriological sa ubmitted	ample submitted to De	epartment?	YES Was W	/ater Well Disinfer			vas sampie NO	
5 TYPE OF CASING USED:	5. Wrought Iron	7. Fiberglass	9. Ot	her (Specify		IG JOINTS: C	Glued	Threaded	
1. Steel 3. RPM (SR) Welded Clamped									
2. PVC 4. ABS	6. Asbestos-Cement		5						
Blank casing diameter 5	in. to 25 ft.		in.	to	,		in. to	ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214									
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENIN	IGS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)									
2. Louvered shutter 4. Key p	punched 6. Wire wrap	pped	8. Sa	w cut	10. Other	(specify)			
SCREEN - PERFORATION INTERVAL	From 25	ft. to	50	ft.,	From	ft.	40	ft.	
	From	ft. to	20	ft.,	From	ft.	to to	rt. ft.	
GRAVEL PACK INTERVALS:	From 24	ft. to	50	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat		nent Grout	3	. Bentonite			onite hole plu		
Constitute rate at A 4 4 4 5 1							~5 ft.		
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7. Pit privy 10. L				k pens					
9 Source lorger 11 Stell storage					16. Other (sp				
2. Sewer lines 5. Cess Pool 5.									
3. Watertight sewer line 6. Seepage plt 9. Feed yard 12. Direction from well? Southwest				oto.ugc	How many feet? 50 ft. plus				
From To	LITHOLOGIC LOG		From	To			GÎC LOG		
0 4 topsoil									
4 18 clay 18 35 fine sand									
35 50 shale							***		
				ļ	···		· · · · · · · · · · · · · · · · · · ·		
	NO.								
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 10/30/2007 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11-2-2007									
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp									