WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Harvey NE NESE 28 24 1E 1/4 1/4 1/4 T S R E/W Distance and direction from nearest town or city street address of well if located within city? 1 1/2 mile North of 125th St. N., West side of Spencer Sedgwick, Kansas DIRKS, Tim WATER WELL OWNER: Board of Agriculture, Division of Water Resource 1000 S. Spencer RR#,ST. ADDRESS,BOX #: Sedgwick, Kansas CITY, STATE: ZIP CODE Application Number 4 DEPTH OF COMPLETED WELL: 50 FLEVATION: LOCATE WELL'S LOCATION ft. WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: fŧ. ft. N WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/30/07 Pump test data: Well water was ft. after hours of pumping @ gpm ΝW NE-Est. Yield: Well water was ft. after hours of pumping @ gpm apm to 50 ≌ 12 Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 12. Other (Specify below) 8. Air conditioning 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES) submitted Was Water Well Disinfected? 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 5. Wrought Iron Fiberglass 1. Steel 3. RPM (SR) Welded Clamped SDR-26 Concrete tile 2. PVC 4. ABS Asbestos-Cement 5 Blank casing diameter 24 Dia. ft., Dia in. to ft. 12 2.35 Weight: Casing height above land surface: in . lbs. / ft. Wall thickness or gauge No. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 11. Other (specify) 9 ABS 3. Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4 Galvanized SCREEN OR PERFORATION OPENINGS ARE 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1. Continuous slot 8. Saw cut 10. Other (specify) 2. Louvered shutter 6. Wire wrapped 4. Key punched 52 24 SCREEN - PERFORATION INTERVAL ft. to ft., From to ft. ft From to ft., From to ft. 25 GRAVEL PACK INTERVALS: ft. to 52 From ft., From ft. to ft. From to ft.. From ft. to ft. **GROUT MATERIALS:** Other bentonite hole plug 1. Neat cement 2. Cement Grout 3. Bentonite 24 Grout Intervals: From From ft. ft ft., From to What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line East How many feet? 100 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τo From Τо topsoil clay 15 4 fine sand 15 25 25 50 shale Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and plugged 10/30/2007 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. This water well record was completed on (mo/day/year) 11-2-2007 Kansas Water Well Contractor's License No. 236 Todd S. Harb by (signature) under the business name of Harp Well and Pump Service