

LOCATION OF WATER WELL:

Fraction

Section Number

Township Number

Range Number

County: HARVEY NE 1/4 SE 1/4 NE 1/4 34 T 24 S R 1 E

Distance and direction from nearest town or city street address of well if located within city?

7 East of Sedg., 3/4 North

WATER WELL OWNER:

Donald Wilson

RR#, St. Address, Box #:

RR#

City, State, ZIP Code

Sedgwick, KS 67135-65

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL

65

ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 15 ft. 2. 12-1-94 ft. 3. 12-1-94 ft.WELL'S STATIC WATER LEVEL 15 ft. below land surface measured on mo/day/yr 12-1-94Pump test data: Well water was 11 ft. after 65 hours pumping 12-1-94 gpmEst. Yield 11 gpm Well water was 65 ft. after 65 hours pumping 12-1-94 gpmBore Hole Diameter 11 in. to 65 ft., and 65 in. to 65 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:

- 1 Steel  
2 PVC  
3 RMP (SR)  
4 ABS

- 5 Wrought iron  
6 Asbestos-Cement  
7 Fiberglass

- 8 Concrete tile  
9 Other (specify below)

CASING JOINTS: Glued X Clamped XWelded XThreaded XBlank casing diameter 12 in. to 12 ft., Dia 2.60 in. to 12 ft., Dia 140 in. to 140 ft.Casing height above land surface 12 in., weight 2.60 lbs./ft. Wall thickness or gauge No. 140 PVC

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel  
2 Brass  
3 Stainless steel  
4 Galvanized steel

- 5 Fiberglass  
6 Concrete tile

- 7 PVC  
8 RMP (SR)  
9 ABS

10 Asbestos-cement

11 Other (specify) 140

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- 1 Continuous slot  
2 Louvered shutter  
3 Mill slot  
4 Key punched

- 5 Gauzed wrapped  
6 Wire wrapped  
7 Torch cut

- 8 Saw cut  
9 Drilled holes  
10 Other (specify)  
11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 65 ft. to 63 ft., From 44 ft. to 29 ft., From 30 ft. to 65 ft.GRAVEL PACK INTERVALS: From 30 ft. to 65 ft., From 30 ft. to 65 ft., From 30 ft. to 65 ft.

GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 03 ft. to 28 ft., From 03 ft. to 28 ft., From 03 ft. to 28 ft.

What is the nearest source of possible contamination:

- 1 Septic tank  
2 Sewer lines  
3 Watertight sewer lines  
4 Lateral lines  
5 Cess pool  
6 Seepage pit

- 7 Pit privy  
8 Sewage lagoon  
9 Feedyard

- 10 Livestock pens  
11 Fuel storage  
12 Fertilizer storage  
13 Insecticide storage  
14 Abandoned water well  
15 Oil well/Gas well  
16 Other (specify below)

Direction from well? NNHow many feet? 120

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil	44	49	clay
2	17	clay	49	59	fine sand
17	29	fine sand	59	65	clay to shale
29	44	gravel			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was

completed on (mo/day/year) 12-4-94 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 318This Water Well Record was completed on (mo/day/yr) 12-28-94under the business name of Weninger Drillingby (signature) Barbara Weninger