

1 LOCATION OF WATER WELL: County: GREENWOOD		Fraction SW 1/4 SW 1/4 NW 1/4	Section Number 33	Township Number T 24 S	Range Number R 11 EW
Distance and direction from nearest town or city street address of well if located within city? 3.5 MS + 2M-W + 1/2 MS OF HAMILTON					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		V.E. SHORT 2108 W 18 EMPORIA KS 66801			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 22 ft. ELEVATION: - Depth(s) Groundwater Encountered 1. UNKNOWN ft. 2. - ft. 3. - ft. WELL'S STATIC WATER LEVEL 16 ft. below land surface measured on mo/day/yr 11-18-89 Pump test data: Well water was - ft. after - hours pumping - gpm Est. Yield 75 gpm: Well water was - ft. after - hours pumping - gpm Bore Hole Diameter 120 in. to 22 ft., and - in. to - ft. WELL WATER TO BE USED AS: 1 <input checked="" type="checkbox"/> Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well *LIVESTOCK Was a chemical/bacteriological sample submitted to Department? Yes - No * If yes, mo/day/yr sample was submitted - Water Well Disinfected? Yes X No -			
5 TYPE OF BLANK CASING USED:		3 Wrought iron 8 Concrete tile CASING JOINTS: Glued - Clamped - 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded - 2 PVC 4 ABS 7 Fiberglass LIME STONE Threaded -			
Blank casing diameter - in. to - ft. Dia. - in. to - ft. Dia. - in. to - ft.		Casing height above land surface - in. weight - lbs./ft. Wall thickness or gauge No. -			
TYPE OF SCREEN OR PERFORATION MATERIAL: NA		7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) - 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: NA		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) -			
SCREEN-PERFORATED INTERVALS: From NA ft. to - ft., From - ft. to - ft.		From - ft. to - ft., From - ft. to - ft.			
GRAVEL PACK INTERVALS: From NA ft. to - ft., From - ft. to - ft.		From - ft. to - ft., From - ft. to - ft.			
6 GROUT MATERIAL: NA 1 Neat cement 2 Cement grout 3 Bentonite 4 Other -		Grout Intervals: From 13 ft. to 12 ft., From - ft. to - ft., From - ft. to - ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage OIL WELLS			
Direction from well? West and NW West		How many feet? SEC 32 (WOMER CREEK)			
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
UNKNOWN		25'			
WELL LOCATED IN 10YR FLOOD PLAIN		GL			
1930'S USED TO WATER LIVESTOCK AND DOMESTIC USE		CLAY			
FOR PEOPLE IN AND AREA OF APPROX 10M DIA. OF SAID WELL -		LIMESTONE WALL - REMOVED TO 10'			
1936 - FILLED TANKS - DAYLIGHT HOUS FOR (EACH DAY) APPROX 6 MONTHS - 2-Piston PUMPS - TRACTOR and a HAND OPERATED.		CLAY			
		GRAVEL FILL			
		6" BENTONITE			
		SWL			
		6'20"			
		10'00"			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-20-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 479 This Water Well Record was completed on (mo/day/yr) 12-11-89 under the business name of EBBERTS DRILLING by (signature) Gregory Ebberts					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4