

County: Greenwood Fraction: NE SE NW SW Sec. 30 T. 24 S R. 13 E

CORRECTION(S) to WATER WELL COMPLETION RECORD Form WWC-5 (to rectify lacking or incorrect information)

Owner: Dobbs, Ian

If location corrected, was listed as:

Section-Township-Range: 24-30-13

Fraction (1/4 calls): SE NW SW SW

Location changed to:

30-24-13 E

NE SE NW SW

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

Verification method: We used the WWC-5 mapper, as well as section 3 of the attached WWC-5 to
correct the quarter calls and the PLSS coordinates.

Initials: BK Date: 1-12-2022

Submitted by: ☒ Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3724
☐ Kansas Dept. of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367

WATER WELL RECORD Form WWC-5

☐ Original Record ☒ Correction ☐ Change in Well Use

Division of Water
Resources App. No.

Well ID

1 LOCATION OF WATER WELL:

County: Greenwood

Fraction

SE 1/4 NW 1/4 SW 1/4

Section Number

24 S 30

Township Number

24 T 30 S

Range Number

R 13 E

2 WELL OWNER: Last Name: Dobbs

First: IAN

Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: ☐

Business: CowSkin Properties

Address: 4590 N Maize Rd

City: Maize


State: KS ZIP: 67101

NW section at EE Rd and 220 Rd

North side of Road 1/4 mile

3 LOCATE WELL WITH "X" IN SECTION BOX:

N



S

4 DEPTH OF COMPLETED WELL: 100 ft.

Depth(s) Groundwater Encountered: 1) 25 ft.

2) ft. 3) ft. or 4) ☐ Dry Well

WELL'S STATIC WATER LEVEL: 10 ft.

☒ below land surface, measured on (mo-day-yr) 8/25/21

☐ above land surface, measured on (mo-day-yr)

Pump test data: Well water was ft.

after hours pumping gpm

Well water was ft.

after hours pumping gpm

Estimated Yield: gpm

Bore Hole Diameter: 8 in. to 100 ft. and

..... in. to ft.

5 Latitude: 37° 55' 48" N (decimal degrees)

Longitude: 96° 01' 39" W (decimal degrees)

Horizontal Datum: ☒ WGS 84 ☐ NAD 83 ☐ NAD 27

Source for Latitude/Longitude:

☐ GPS (unit make/model:) (WAAS enabled? ☐ Yes ☐ No)

☐ Land Survey ☐ Topographic Map

☐ Online Mapper:

6 Elevation: ft. ☐ Ground Level ☐ TOC

Source: ☐ Land Survey ☐ GPS ☐ Topographic Map

☐ Other

7 WELL WATER TO BE USED AS:

1. Domestic:

☒ Household

☐ Lawn & Garden

☐ Livestock

2. ☐ Irrigation

3. ☐ Feedlot

4. ☐ Industrial

5. ☐ Public Water Supply: well ID

6. ☐ Dewatering: how many wells?

7. ☐ Aquifer Recharge: well ID

8. ☐ Monitoring: well ID

9. Environmental Remediation: well ID

☐ Air Sparge ☐ Soil Vapor Extraction

☐ Recovery ☐ Injection

10. ☐ Oil Field Water Supply: lease

11. Test Hole: well ID

☐ Cased ☐ Uncased ☐ Geotechnical

12. Geothermal: how many bores?

a) Closed Loop ☐ Horizontal ☐ Vertical

b) Open Loop ☐ Surface Discharge ☐ Inj. of Water

13. ☐ Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☒ No If yes, date sample was submitted:

Water well disinfected? ☒ Yes ☐ No

8 TYPE OF CASING USED: ☐ Steel ☒ PVC ☐ Other

Casing diameter 5 in. to 100 ft., Diameter in. to ft.

Casing height above land surface 1.8 in. Weight lbs./ft. Wall thickness or gauge No. SDR 21

TYPE OF SCREEN OR PERFORATION MATERIAL:

☐ Steel

☐ Stainless Steel

☐ Fiberglass

☒ PVC

☐ Other (Specify)

☐ Brass

☐ Galvanized Steel

☐ Concrete tile

☐ None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

☐ Continuous Slot

☐ Mill Slot

☐ Gauze Wrapped

☐ Torch Cut

☐ Drilled Holes

☐ Other (Specify)

☐ Louvered Shutter

☐ Key Punched

☐ Wire Wrapped

☒ Saw Cut

☐ None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 80 ft. to 100 ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 100 ft. to 20 ft., From ft. to ft.

9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☒ Bentonite ☐ Other

Grout Intervals: From 0 ft. to 20 ft., From ft. to ft.

Nearest source of possible contamination: None

☐ Septic Tank

☐ Lateral Lines

☐ Pit Privy

☐ Livestock Pens

☐ Insecticide Storage

☐ Sewer Lines

☐ Cess Pool

☐ Sewage Lagoon

☐ Fuel Storage

☐ Abandoned Water Well

☐ Watertight Sewer Lines

☐ Seepage Pit

☐ Feedyard

☐ Fertilizer Storage

☐ Oil Well/Gas Well

☐ Other (Specify)

Direction from well? Distance from well? ft.

10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS

0 2 TOPSOIL 85 100 SHALE

02 23 SHALE

23 28 LINE H2O

28 33 SHALE

33 42 LINE

42 63 SHALE

63 67 LINE

67 80 SHALE

80 85 LINE

Notes:

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged

under my jurisdiction and was completed on (mo-day-yr) 8/25/21 and this record is true to the best of my knowledge and belief.

Kansas Water Well Contractor's License No. 975 This Water Well Record was completed on (mo-day-yr) 8/25/21

under the business name of Enders Water Well Drilling Signature [Signature]

Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section,

1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.

Visit us at <http://www.kdheks.gov/waterwell/index.html>

KSA 82a-1212

Revised 7/10/2015



Due to unconsolidated
formation - River gravel,

WESTERN HYDRO I top set this well with
8 5/8 steel casing. A 15' borehole was drilled to
32', top of River gravel. 8 5/8 casing was
driven to bed rock at 37'. The well was then
drilled to 50' with 7 7/8 bit. 5" pvc was
perforated from 50' to ~~20'~~^{21'}. 8 5/8 was
perforated from 37' to ~~20'~~^{21'}. Gravel pack
was placed inside 8 5/8 from 50' to 20'.
Gravel pack was placed ~~in~~ outside 8 5/8
from 32' to 20'. Bentonite grout was
used inside both Annulus from 20' to
Surface. 8 5/8 was cut off at surface.
5" pvc was cut off at 18" above
Surface. Static level is 11'. APPX GPM
50 +

01/11/17

01/11/17