

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Allen</u>	<u>SW 1/4 SE 1/4 NE 1/4</u>	<u>27</u>	T <u>24</u> S	R <u>18</u> <u>EW</u>

Distance and direction from nearest town or city street address of well if located within city?

801 N. Industrial Road Iola, KS2 WATER WELL OWNER: City of IolaRR#, St. Address, Box # : 801 N. Industrial Road
City, State, ZIP Code : Iola, KS 66749Board of Agriculture, Division of Water Resources
Application Number:3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL 15 ft. ELEVATION: 960.64Depth(s) Groundwater Encountered 1 ft. 2 7.88 ft. 3 7.22/04 ft.
WELL'S STATIC WATER LEVEL 7.88 ft. below land surface measured on mo/day/yr 7/22/04Pump test data: Well water was 1 ft. after 1 hours pumping 1 gpm
Est. Yield 1 gpm: Well water was 1 ft. after 1 hours pumping 1 gpmWELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well M.W. 8Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No X5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 1 Clamped 11 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 1
2 PVC 4 ABS 7 Fiberglass Threaded 1Blank casing diameter 2 in. to 5 ft. Dia 5 in. to 5 ft. Dia 5 in. to 5 ft.Casing height above land surface FNH in., weight 5.12 d 40 lbs./ft. Wall thickness or gauge No. 1

TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement

1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 1
2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 1 ft.SCREEN-PERFORATED INTERVALS: From 5 ft. to 15 ft. From 1 ft. to 1 ft.GRAVEL PACK INTERVALS: From 3 ft. to 15 ft. From 1 ft. to 1 ft.From 1 ft. to 1 ft. From 1 ft. to 1 ft.6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 1Grout Intervals: From 1 ft. to 3 ft. From 1 ft. to 1 ft. From 1 ft. to 1 ft.

What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well

1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) Contaminated site3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
Direction from well? How many feet?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

9 10 Asphalt 9 1010 15 Asphalt, concrete, Gravel, Clay fill 10 1510 15 Red clay 10 157 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/24 7/16/04 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's Licence No 704 This Water Well Record was completed on (mo/day/yr) 8/3/04
under the business name of MAXS by (signature) Ray Plummer