

1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 NW 1/4 SW Section Number 26 Township Number T 24 S Range Number R 18 EW
 County: Allen

Distance and direction from nearest town or city street address of well if located within city?
601 North State Street Iola, KS 66749

2 WATER WELL OWNER: Sigg Brothers
 RR#, St. Address, Box # : 601 North State Street Iola, KS 66749 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Iola, KS 66749 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: X in SW quadrant of NW 1/4 section.
 4 DEPTH OF COMPLETED WELL 12.74 ft. ELEVATION: 962.05
 Depth(s) Groundwater Encountered 1 10.05 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 952.00 ft. below land surface measured on mo/day/yr 1/11/05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well MW-05
 Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
2 PVC 4 ABS 7 Fiberglass Welded
 6 Asbestos-Cement 9 Other (specify below) Threaded X
 Blank casing diameter 2 in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface -0.22 in., weight lbs./ft. Wall thickness or gauge No. sch 40
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 2.74 ft. to 12.74 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 2.74 ft. to 12.74 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0.5 ft. to 2.74 ft., From 2.74 ft. to 12.74 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)
 Direction from well? west How many feet? 35-40 ft

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
1	2	med to high plastic clay, stiff, dark brown, dry			
4	5	med to high plastic clay, stiff, dark brown, dry			
9	10	high plastic clay, tan, stiff, Fe2 staining, sand zone			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1/10/05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 204 This Water Well Record was completed on (mo/day/yr) 1/14/05 under the business name of man by (signature) David Skempke

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.