T. T				R WELL RECOF	RD For	m WWC-5		2a-1212			
	TION OF WA	TER WELL:	Fraction			Sec	tion Numbe		hip Number	Range Number	
County:			NE 1/4		<u>NE</u>	1/4	34	T2	924s	R 18 (E)W	
1		n from nearest town Southeast of th				,					
		vnen: Hampel (<u> </u>	<i>J</i> <u> </u>					
	Address, Bo	•		001 9 27104				Roar	d of Agricultura	Division of Water Because	
City, State, ZIP Code Iola, Kansas 66749						Board of Agriculture, Division of Water Resource Application Number:					
3 LOCA	TE WELL'S I " IN SECTIO	OCATION WITH 4 IN BOX:	DEPTH OF Control	OMPLETED WE	LL	15 12	ft. ELEV	'ATION:			
7	<u> </u>	I X V	VELL'S STATIC	WATER LEVEL	8.12	ft h	elow land s	urface measur	ed on mo/day/yr		
1 }	1	1 ' 1 1	Pum	n test data: We	ll water ws		64 ft	after	bourg as	mping gpn	
	NW	NE	st. Yield	anm: We	ll water we	 	#.	after	hours pu	imping gpn	
	1 .		Bore Hole Diame	eter 7 5/8	in to	15	ft	and	in in incurs po	, to	
Mi w		E V	VELL WATER 1	O BE USED AS		ublic wate			oning 11		
-	•		1 Domestic	3 Feedlot						Other (Specify below)	
	SW	SE	2 Irrigation	4 Industria						······································	
	1		-							, mo/day/yr sample was su	
<u>+</u>			nitted	odoteriological sa	imple subil	inted to Di		ater Well Disir			
5 TYPE	OF BLANK	CASING USED:	nttou	5 Wrought iron		9 Copper			· · · · · · · · · · · · · · · · · · ·	No X	
1 S		3 RMP (SR)		6 Asbestos-Cer						d Clamped ,	
(2)P		4 ABS			ment		(specify belo	,		ed	
			. to E	7 Fiberglass						aded	
										in. to ft	
				.in., weight		(1)	lbs			o sch. 40	
		R PERFORATION		(z)evc					10 Asbestos-cement		
1 Steel 3 Stainless steel				5 Fiberglass 8 RMP (SR)				11 Other (specify)			
2 Brass 4 Galvanized steel				6 Concrete tile 9 ABS			S		None used (op	•	
		RATION OPENINGS						8 Saw cut		11 None (open hole)	
	ontinuous sid			6	Wire wrap	ped		9 Drilled h			
	ouvered shut	,			Torch cut			10 Other (s	pecify)		
SCREEN-	PERFORAT	ED INTERVALS:	From	.D ft.	to	ŤĎ.	ft., Fr	om ,	ft. t	o	
		•	From	ft.	to		ft., Fr	om	ft., t	o	
	GRAVEL PA	CK INTERVALS:	From	.4 ft.	to	. 1 5				o	
			From	Mrs.	to		ft., Fr	om		o ft	
E GROU	T MATERIAL	.: 1 Neat cer	ment (2 Cement grout	•	(3)Bento	nite 4	Other			
Grout Inte	rvals: Fro	mft.	. to	ft., From .		ft.	to	ft., Fro	m	ft. to	
What is th	ne nearest so	ource of possible co	intamination:				10 Live	stock pens	14 A	bandoned water well	
1 Septic tank 4 Lateral lines				7 Pit priv	y	(11)Fuel storage			15 Oil well/Gas well		
2 Sewer lines 5 Cess pool			001	9 9			12 Fertilizer storage			16 Other (specify below)	
3 Watertight sewer lines 6 Seepage			je pit	pit 9 Feedyard			13 Insecticide storage				
Direction		Southwest					How m	any feet?	110		
FROM	ТО	····	LITHOLOGIC	LOG		FROM	ТО		PLUGGING II	NTERVALS	
0	6"	Concrete						···			
6"	4	Cly, drk brn,			, f-c						
		grnd & mod gr									
4	7	Cly, It olv b	orn, v slty,	damp, sl pls	tc						
7	15	Cly, lt olv -									
		moist									
	į i									12 11 15 13 14 14 14 14 14 14 14 14 14 14 14 14 14	
		···			1						
Jacobs Maria Company											
								Mw	2 - Flushmu	nt cover	
									2 - Flushmou	nt cover	
									2 - Flushmou n Taylor	nt cover	
										nt cover	
										nt cover	
								Do	n Taylor		
Z CONTI	RACTOR'S (DR LANDOWNER'S						Do	n Taylor (3) plugged und	er my jurisdiction and was	
completed	on (mo/day/	year)10-2	21-94				and this rec	onstructed, or	n Taylor (3) plugged und	er my jurisdiction and was	
completed Water We	on (mo/day/	year)	21-94	This Wa			and this rec	onstructed, or ord is true to the on (mo/day/yr	n Taylor (3) plugged und	er my jurisdiction and was	