

<b>1 LOCATION OF WATER WELL:</b>		Fraction	Section Number		Township Number	Range Number
County: Allen	NE ¼ NE ¼ NE ¼	34	T	29 24 S	R	18 EW
Distance and direction from nearest town or city street address of well if located within city? 160 feet East of the SE corner of Davis St. & Hwy 54						
<b>2 WATER WELL OWNER:</b> Hampel Oil Distributor, Inc.						
RR#, St. Address, Box # : 503 West St. City, State, ZIP Code : Iola, Kansas 66749						
Board of Agriculture, Division of Water Resources Application Number:						
<b>3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:</b>	<b>4 DEPTH OF COMPLETED WELL:</b> 15 ft. <b>ELEVATION:</b> 12 ft.					
	Depth(s) Groundwater Encountered 1. 12 ft. 2. ft. 3. ft.					
	WELL'S STATIC WATER LEVEL 6.16 ft. below land surface measured on mo/day/yr					
	Pump test data: Well water was ft. after hours pumping gpm					
	Est. Yield gpm: Well water was ft. after hours pumping gpm					
	Bore Hole Diameter 7.5/8 in. to 15 ft., and in. to ft.					
<b>WELL WATER TO BE USED AS:</b>						
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted						
<b>5 TYPE OF BLANK CASING USED:</b>						
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded						
Blank casing diameter 2 in. to 5 ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. sch. 40						
<b>TYPE OF SCREEN OR PERFORATION MATERIAL:</b>						
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement						
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
SCREEN-PERFORATED INTERVALS: From 5 ft. to 15 ft. From ft. to ft.						
GRAVEL PACK INTERVALS: From 3 ft. to 15 ft. From ft. to ft.						
<b>6 GROUT MATERIAL:</b> 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 0 ft. to 2 ft. From 2 ft. to 3 ft. From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
Direction from well? Southeast How many feet? 100						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	2	Cly, lt - med brn, v slty, v grvly, mod f-c snd, dry				
2	9	Cly, drk brn, mod slty, moist				
9	15	Cly, lt brn, mott w/ lt gry & mod rust stains, v slty, v plstc, moist				
MW4 - Flushmount Don Taylor						
<b>7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:</b> This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-21-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 10-24-94 under the business name of GeoCore Services, Inc. by (signature)						