

1 LOCATION OF WATER WELL: County: Harvey NW 1/4 SW 1/4 SW 1/4 Section 8 Township 24 S Range 20 E  
Distance and direction from nearest town or city street address of well if located within city?  
1 mile west & 1/4 mile north of Whitewater Rd #81

2 WATER WELL OWNER: Randy Matthews  
RR#, St. Address, Box #: PO Box 1112  
City, State, ZIP Code: Newton, KS 67114  
Board of Agriculture, Division of Water Resources  
Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
N  
NW NE  
W X SW SE  
S

4 DEPTH OF COMPLETED WELL 65 ft. ELEVATION:  
Depth(s) Groundwater Encountered 24 ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL 24 ft. below land surface measured on mo/day/yr 11-20-97  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield 30 gpm Well water was ft. after hours pumping gpm  
Bore Hole Diameter 11 in. to 65 ft. and in. to ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter 5 in. to 45 ft. Dia 2.40 in. to ft. Dia in. to ft.  
Casing height above land surface 12 in. weight 2.40 lbs./ft. Wall thickness or gauge No. 160 PSI  
TYPE OF SCREEN OR PERFORATION MATERIAL:  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)  
12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE:  
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 45 ft. to ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 24 ft. to 65 ft. From ft. to ft.  
From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 3 Neat cement 2 Cement grout 5 Bentonite 4 Other  
Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? How many feet?  
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS  
0 34 clay  
34 49 fine sand  
49 50 clay  
50 53 sand  
53 65 shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-20-97 and this record is true to the best of my knowledge and belief. Kansas  
Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 11-20-97  
under the business name of Weneringer Drilling Inc. by (signature) Michael Gorgis

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.