		· <u> </u>	WATE	R WELL RECORD	Form WWC-5	KSA 82	a-1212	·		
LOCATION OF WATER WELL:			Fraction			Section Number		Number	Range Number	
County:		Allen	NE 1/4			2.0	J T 24	<u> </u>	R 21E E/W	
Distance an	nd direction	from nearest to	wn or city street a	ddress of well if located	I within city?					
 			northeast	of Moran, I	KS					
	WELL OW	KOI	bert Moran	n'						
	ddress, Box	* # : RR		KS 66755 Board of Agriculture, Division of Water Reso					Division of Water Resource	
City, State,		<u> </u>		<u> </u>				tion Number:		
LOCATE	WELL'S LON N SECTION	CATION WITH								
Ī	l x	- NE	WELL'S STATIC Pum Est. Yield 1	WATER LEVEL; test data: Well water 0. gpm: Well water	3.2 ft. bir was	elow land su ft. a	rface measured after	on mo/day/yr hours pu hours pu	3ft. umpinggpm umpinggpm	
w -	1	F							n. to	
Σ "	!	! 1	WELL WATER 1		5 Public wate	supply	8 Air condition		Injection well	
	_ sw	SE -	1 Domestic	~ *			9 Dewatering		Other (Specify below)	
.	1	ī	2 Irrigation		_	-				
.			Was a chemical/	bacteriological sample s	ubmitted to De				s, mo/day/yr sample was sub	
L	<u> </u>	-	mitted	· · · · · · · · · · · · · · · · · · ·	****	W	ater Well Disinfe	cted? Yes	X No	
TYPE O	F BLANK C	ASING USED:		5 Wrought iron	8 Concre	te tile	CASING	JOINTS: Glue	d X Clamped	
1 Ste	el	3 RMP (S	SR)	6 Asbestos-Cement	9 Other	specify belo	w)	Weld	ded	
X 2 PV		4 ABS		7 Fiberglass					aded	
									in. to ft.	
Casing heig	ght above la	ind surface	.1.8	.in., weight		Ibs	/ft. Wall thicknes	ss or gauge N	₀.sch.40	
TYPE OF S	SCREEN OF	R PERFORATIO	N MATERIAL:		X 7 PV	2	10 /	Asbestos-cem	ent	
1 Steel 3 Stainless steel				5 Fiberglass	8 RM	P (SR)	(SR) 11 Other (specify)			
2 Brass 4 Galvanized steel				6 Concrete tile	6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN C	R PERFOR	RATION OPENIN	NGS ARE:	5 Gauze	ed wrapped		8 Saw cut		11 None (open hole)	
1 Cor	ntinuous slo	t <u>X3N</u>	∕lill slot	6 Wire v	vrapped		9 Drilled hole	es		
2 Lou	vered shutt	er 4 k	Key punched	7 Torch	cut		10 Other (spe	cify)		
SCREEN-P	PERFORATE	D INTERVALS:	: From 2!	O ft. to	4.0	ft., Fro	om	ft:	toft	
			From	ft. to		ft., Fro	om	, , ., , , , , ft,	toft	
Ġ	RAVEL PA	CK INTERVALS	: From 2.	D ft. to	1 0.0	ft., Fro	om	ft.	toft	
			From	ft. to		ft., Fro	óm	ft.	to fi	
6 GROUT	MATERIAL	: X 1 Neat	cement	2 Cement grout	3 Bento	nite 4	Other			
Grout Inten	vals: From			ft., From	ft.	to	ft., From	<i></i>	ft. to	
			contamination:	•			stock pens		Abandoned water well	
			7 Pit privy				15 Oil well/Gas well			
	1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertilizer storage			16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit				y 9 Feedyard		13 Insecticide storage				
Direction fr	-	East	page pit	A			any feet?		50	
FROM	TO		LITHOLOGIC	LOG	FROM	то	arry toot:	PLUGGING	INTERVALS	
Ö	9	Soi1/Re							unione de la companya de la company	
9	19	Lime	the state of the s	· · · · · · · · · · · · · · · · · · ·			., / , 		<u></u>	
19	23	Yellow	clav	, iii 			· · · · · · · · · · · · · · · · · · ·			
23	32		ale (Wate	r)	·			 		
32	37	Lime		The second secon					the state of the s	
37	47	Shale								
47	50	Lime						A.MA-1117 TERRITOR	· · · · · · · · · · · · · · · · · · ·	
50	77	Shale								
77	83	Lime						and the same of th		
83	100		TD							
	T 0 0	DHATE	11/							
		1-1-1-1			- I amena iran 4					
									And the second s	
	- interest								_ · · · · · · · · · · · · · · · · · · ·	
	L					L	L			
10/2007									nder my jurisdiction and wa	
completed	on (mo/day	/year) 5/3	1/94			and this red	ord is true to the	e best of my k	nowledge and belief. Kansa	
completed	on (mo/day	/year) 5/3	1/94			and this red	ord is true to the l on (mo/day/yr)	best of my k	nowledge and belief. Kansa	