

LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 SE 1/4 Section Number 29 Township Number T 24 S Range Number R 21 E
 County: Allen
 Distance and direction from nearest town or city street address of well if located within city?

3 miles East Moran, Kansas


WATER WELL OWNER: Ferdinand Lampe

R#, St. Address, Box #: RRI
 City, State, ZIP Code: Moran, Kans 66755

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: DEPTH OF COMPLETED WELL: 150 ft. ELEVATION:



Depth(s) Groundwater Encountered 1. 35-42 ft. 2. 125-128 ft. 3. 6/20/81

WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 1 ft. after 8 1/4 hours pumping 150 gpm

Est. Yield 1 gpm: Well water was 150 ft. after 8 1/4 hours pumping 150 gpm

Bore Hole Diameter 8 1/4 in. to 150 ft., and 150 in. to 150 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:

1 Steel 3 RMP (SR)
 2 PVC 4 ABS

5 Wrought iron 6 Asbestos-Cement 7 Fiberglass

8 Concrete tile 9 Other (specify below)

CASING JOINTS: Glued X Clamped X

Welded X

Threaded X

Blank casing diameter 6 in. to 32 ft., Dia. 12 in. to 150 ft., Dia. 255 lbs./ft. Wall thickness or gauge No. 255

Casing height above land surface 12 in., weight 12 lbs./ft.

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass
 2 Brass 4 Galvanized steel 6 Concrete tile

7 PVC 8 RMP (SR) 9 ABS

10 Asbestos-cement 11 Other (specify)

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot 3 Mill slot
 2 Louvered shutter 4 Key punched

5 Gauzed wrapped 6 Wire wrapped 7 Torch cut

8 Saw cut 11 None (open hole)

9 Drilled holes

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 32 ft. to 150 ft., From 12 ft. to 150 ft.

From 12 ft. to 150 ft., From 12 ft. to 150 ft.

GRAVEL PACK INTERVALS: From 12 ft. to 150 ft., From 12 ft. to 150 ft.

From 12 ft. to 150 ft., From 12 ft. to 150 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 3 ft. to 14 ft., From 14 ft. to 150 ft., From 14 ft. to 150 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy
 2 Sewer lines 5 Cess pool 8 Sewage lagoon
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard

10 Livestock pens 14 Abandoned water well
 11 Fuel storage 15 Oil well/Gas well
 12 Fertilizer storage 16 Other (specify below)

13 Insecticide storage

How many feet? Approx 75'

Direction from well?

FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG

0	2	Soil			
2	4	Sand Hard			
4	10	Clay			
10	12	Lime			
12	35	Shale Blue			
35	60	Lime Shells			
60	125	Lime - Thin layers Shale			
125	128	Shale Blue - WATER			
128	150	Lime			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/20/81 and this record is true to the best of my knowledge and belief. Kansas

Water Well Contractor's License No. 377 This Water Well Record was completed on (mo/day/yr) 7/18/81

Under the business name of Nichols WTR Well Drilling by (signature) Burt Nichols

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.