			WATER	WELL RECORD F	orm WWC-5	KSA 82	2a-1212				
	Bourb	TER WELL:	Fraction 1/	NW 14 SE	See	ction Numbe	1	nip Number	Range N	_ ^	
Distance a	nd direction	from nearest town of	or city street add	ress of well if located			<u> </u>	T 3	_ 11	9	
		5. of Ma			,						
	R WELL OW		Teffcoat						Paul Pale von Green		
_		(# Rt. 2	-		,		Board	l of Agriculture, (Division of Wate	er Resources	
	, ZIP Code		eton k	LS 66754	l			cation Number:			
3 LOCATE		OCATION WITH 4	DEPTH OF CO	MPLETED WELL	229	ft. ELEV	ATION: //01	Known			
- ~ ~	IN SECTION	1 (De	epth(s) Groundwa	ater Encountered 1.	/5/	ft.	. 2	ft. 3		ft.	
Ī l	1	! W	ELL'S STATIC W	ATER LEVEL7	tt. t	elow land s	urface measure	ed on mo/day/yr	OCF. 12	1993	
-	- NW	NE	- 1/	est data: Well water		,					
	1			. gpm: Well water							
w wie				r 9 in. to .						ft.	
₹ "	!	7! WE	ELL WATER TO		Public water			-	Injection well		
ī L	- SW	SE	Domestic				9 Dewaterin		Other (Specify		
	1	ï	2 Irrigation			-		well		1	
1 L	1	Wa	as a chemical/ba	cteriological sample su	bmitted to D	•			mo/day/yr sam	iple was sub-	
-			tted				Vater Well Disir		No		
5 TYPE C	OF BLANK (CASING USED:	5	Wrought iron	8 Concr	ete tile	CASING	G JOINTS: Glued	1 🖊 Clamp	oed	
1 Ste		3 RMP (SR)	6	Asbestos-Cement	9 Other	(specify bel	ow)	Weld	ed		
2 PV	C	4 ABS		⁷ Fiberglass					aded		
				ft., Dia							
Casing hei	ght above la	and surface	<i>18</i> ir	n., weight Sch	40	lbs	s./ft. Wall thickr	ess or gauge N	o		
TYPE OF	SCREEN O	R PERFORATION M	MATERIAL:		O PV	'C	10	Asbestos-ceme	ent		
1 Ste	eel	3 Stainless st	eel 5	5 Fiberglass 8 RMF			11 Other (specify)				
2 Bra	ass	4 Galvanized	steel 6	6 Concrete tile	9 AE	S	12	None used (op	en hole)		
SCREEN (OR PERFO	RATION OPENINGS	ARE:	5 Gauzeo	dwrapped		8 Saw cut		11 None (ope	n hole)	
1 Co	ntinuous slo	t 3 Mill s	slot	6 Wire w	rapped		9 Drilled h	oles		i	
2 Lo	uvered shut	er 4 Key p	punched	7 Torch o			10 Other (s	pecify)			
SCREEN-F	PERFORATI	ED INTERVALS:	From / 4	2.9 ft. to	229	ft., Fr	rom	ft. t	o	ft.	
			From	ft. to		ft., Fr	rom	ft. t	.o	ft.	
	BRAVEL PA	CK INTERVALS:	From	O ft. to	229	ft., Fr	rom	ft. t	.o		
			From	ft. to		ft., Fr		ft. t		ft.	
6 GROUT	MATERIAL	.: 1 Neat cem	nent 2	Cement grout	3 Bento						
Grout Inter				ft., From	ft.						
What is the		ource of possible cor		,			estock pens	•	bandoned wate	Į.	
1 Se	ptic tank	4 Lateral II	ines 200'	7 Pit privy			el storage		15 Oil well/Gas well		
	wer lines	5 Cess po	_	8 Sewage lagoo	on		tilizer storage	16 Other (specify below)			
		er lines 6 Seepage					nsecticide storage				
Direction for	•	ooo o ooopaga	- F.	0 · 000, 0				sabove.			
FROM	TO		LITHOLOGIC LO	DG	FROM	TO		PLUGGING II	NTERVALS		
0	5	Clay			147	151	Bluck	Slate			
5	15	Sundston	ne.		151	229		shale		,	
5	18	Shale				1					
18	42	Limeston									
18 42	53	Gray Shi			İ	†					
<u> </u>	3 7	Siure	018								
53 57	58	Limeston									
21	65										
58 65 71	71		Shale		 	 					
71		7			<u> </u>	t					
-//	76	Gray LI	nestone	<u> </u>		 	<u> </u>				
76	77	gray Sh	die.		<u> </u>	 					
77	86		Limes	rone							
86	88		restone		L						
88	89	BIK. SIG	te								
89	147	Gray Si	bale			L	L				
7 CONTE	RACTOR'S	OR LANDOWNER'S	CERTIFICATION	N: This water well was	s (①constru	icted, (2) re	constructed, or	(3) plugged und	der my jurisdicti	on and was	
completed	on (mo/day	/year) . <i>Oct /</i> .	3,1995					ne best of my kn			
		s License No. 59		This Water We	II Record wa						
		me of Jess e	,	. /	inc	by (sign		4. QQe	- you	h	
				MLY and PRINT clearly. Pleas	se fill in blanks.			vers. Send top three	copies to Kansas D	Department	
of Hoolt				001. Telephone: 913-296-554					â.		