

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Butler</u>		<u>NE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$ <u>NW</u> $\frac{1}{4}$	<u>18</u>	T <u>24</u> S	R <u>3</u> <u>EW</u>
Distance and direction from nearest town or city street address of well if located within city?					
<u>219 N. Main, Whitewater, KS.</u>					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box # :		Application Number:			
City, State, ZIP Code :					
<u>Marian, KS. 66861</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>17'6"</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered <u>1'4"</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>9'80</u> ft. below land surface measured on mo/day/yr <u>5-1-96</u>			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>8'6"</u> in. to <u>17'6"</u> ft., and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X		If yes, mo/day/yr sample was submitted			
Water Well Disinfected? Yes.....No.....X					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter <u>2.375</u> in. to <u>7'3"</u> ft., Dia		7 Fiberglass	Threaded.....X		
Casing height above land surface <u>Flush Mt.</u> in., weight		lbs./ft. Wall thickness or gauge No. <u>SDR 13</u> ft.			
TYPE OF SCREEN OR PERFORATION MATERIAL:		10 Asbestos-cement			
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped			
1 Continuous slot		3 Mill slot	6 Wire wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	7 Torch cut	9 Drilled holes	10 Other (specify)
SCREEN-PERFORATED INTERVALS:		From <u>17'3"</u> ft. to <u>7'3"</u> ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From <u>17'6"</u> ft. to <u>5'6"</u> ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement			
Grout Intervals: From <u>5'6"</u> ft. to <u>4'</u> ft., From <u>4'</u> ft. to <u>0'</u> ft., From ft. to ft.		2 Cement grout			
What is the nearest source of possible contamination:		3 Bentonite			
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? <u>East</u>		13 Insecticide storage			
		How many feet? <u>50'</u>			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	.75	Gravel			
.75	2	Dk brn-blk. silty clay, earthy odor, moist.			
2	4	Red brn oxide stained clay, tight, no odor w/ gray clay mottling.			
4	8	Gray brn sandy clay, mottled, no odor, firm, fine grained sand.			
8	12	Blue gray mottled silty clay w/ trace amt. of fine grained sand, moist, mod. odor.			
12	14.50	Tan brn silty clay, moist to wet, strong odor w/ fine grained sand len at 14', wet.			
14.50	17'6	Fine grained blk. sand, wet, strong odor.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>5-1-96</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>539</u> This Water Well Record was completed on (mo/day/yr) <u>5-8-96</u> under the business name of <u>JB Environmental Drilling</u> by (signature) <u>James Belk</u>					