

1 LOCATION OF WATER WELL: County: Butler		Fraction NE 1/4 SW 1/4 NW 1/4	Section Number 18	Township Number T 24 S	Range Number R 3 E
Distance and direction from nearest town or city street address of well if located within city? 219 N. Main, Whitewater, KS.					
2 WATER WELL OWNER: Alan Church		RR#, St. Address, Box # : Rt 2 #5 Cherry			
City, State, ZIP Code : Marian, KS. 66861		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 22' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 13' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 11.65 ft. below land surface measured on mo/day/yr 5-2-96			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter: 8 1/2" in. to 22' ft. and in. to ft.			
WELL WATER TO BE USED AS:		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X		If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass		8 Concrete tile 9 Other (specify below) Welded Threaded X			
Blank casing diameter 2.375 in. to 7' ft. Dia.		SDR 1.3 ft.			
Casing height above land surface Flush Mt. in., weight		lbs./ft. Wall thickness or gauge No. SCH 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC			
1 Steel 3 Stainless steel 5 Fiberglass 2 Brass 4 Galvanized steel 6 Concrete tile		8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS:		From 22' ft. to 7' ft. From ft. to ft. From ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS:		From 22' ft. to 5' ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 5' ft. to 3' ft. From 3' ft. to 0' ft. From ft. to ft.			
What is the nearest source of possible contamination:		1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below)			
Direction from well? North		How many feet? 400'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Grass-dk brn to blk. silty clay, firm, earthy odor.			
3	5	Gray brn clay w/ dk brn & oxide stained banding, moist, firm, no odor.			
5	7.50	Red brn silty clay, moist, no odor, oxide stained clay.			
7.50	11	Red brn silty sand, fine grained, moist, no odor, low plasticity.			
11	19	Fine-coarse sand & gravel, no odor, wet at 13', subrounded.			
19	22	Gray-green gray silt, soft, moist to wet, faint odor, highly plastic/.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-2-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 539 This Water Well Record was completed on (mo/day/yr) 5-8-96 under the business name of JB Environmental Drilling by (signature) James Butler					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					