	WATER WELL RE	CORD Fo	rm WW	C-5 KS	A 82a-121	2			
1 LOCATION OF WATER WELL:	FRACTION		SECTION	ON NUMBER	TOWNSHIP	NUMBER	RANGE NUM	BER	
Butler Butler	NW 1/4 SW		1/4	14	T 24	S	R 3E	E/W	
Distance and direction from nearest town or city street address of well if located within city?									
Remington Rd. & 90th, 1/4 m. N. (5 m. E. of Whitewater, 1/14 m. N. of Hwy 196) 2 WATER WELL OWNER: OLDFATHER, Justin									
	Poord of Agricultura, Division of Mater Popular								
	**** * * * * * * * * * * * * * * * * *								
	DEPTH OF COMPLETED W	'FII: 95	ft.		ELEVATION:	Application reality	301.		
WITH AN "X" IN SECTION BOX:	oth of groundwater Encounte		ft,			ft.		ft.	
 	ELL'S STATIC WATER LEVE	22		VI AND SHE	RFACE MEASUR		ay/yr: 7/18/0		
NE NE	Pump test dat	-		V LAND SUI	ft. after		of pumping @	gpm	
 	Est. Yield: gpm	Well water			ft. after		of pumping @	gpm	
₩ E Bo	ore Hole Diameter 12	in.	to 95	5 ft.	and	in.	to	ft.	
-	LL WATER TO BE USED A			7.4		9. Dewaterin	g 11. Injectio	on well	
	1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 12. Other (Specify below)								
	2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample								
submitted Was Water Well Disinfected? YES NO									
TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass 9. Other (Specify below) CASING JOINTS: Glued Threaded									
1. Steel 3. RPM (SR) Welded Clamped									
2. PVC 4. ABS	6. Asbestos-Cement	Concrete tile		. 20					
· ·	in. to 35 ft.,		in.	to	ft., D	ia. ir	n. to	ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214									
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)									
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)									
SCREEN OR PERFORATION OPENING 1. Continuous slot 3. Mill slo		ranned	7 Tor	ch cut	9 Drille	d holes	11. None (ope	n hole)	
2. Louvered shutter 4. Key pu		•			iu. Otnei	(specify)			
SCREEN - PERFORATION INTERVAL	From 35	ft. to	95	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
GRAVEL PACK INTERVALS:	From 24	ft. to	95	ft.,	From	ft.	to	ft.	
	From	ft. to		ft.,	From	ft.	to	ft.	
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite hole plug									
Grout Intervals: From 4		ft., From	ft.	to	ft.,	From	ft. to	ft.	
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas we						well			
1. Septic tank 4. Lateral lines 7. Fit privy 10. Electrock period 13. Insecticide storage 13. On wein das wein 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)									
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage									
Direction from well? Northwest				How many feet? 125					
From To I	LITHOLOGIC LOG		From	То		LITHOLO	GIC LOG		
0 2 topsoil									
2 41 brown shale 41 95 grey shale						-			
41 95 grey shale									
									
7									
Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and									
was completed on (mo/day/year) 7-18-2003 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7-21-2003									
under the business name of Harp Well & Pump Service Inc. by (signature)									