


LOCATION OF WATER WELL:		WATER WELL RECORD		Form WWC-5		KSA 82a-1212	
County: Butte	Fraction NE 1/4 NW 1/4	Section Number 16	Township Number T 24 S	Range Number R 3 E			
Distance and direction from nearest town or city street address of well if located within city? from Numan E on 1st 14 1/2 M = E and 4 1/2 S = 1/4 W on S = S							
WATER WELL OWNER: Triple T Livestock Box 134B Whitewater Kansas			Board of Agriculture, Division of Water Resources Application Number:				
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 77 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr Aug 15 1990					
		Pump test data: Well water was 35 ft. after 1 hours pumping 12 gpm					
		Est. Yield 12 gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 8 in. to 77 ft. and in. to ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Livestock					
		Was a chemical/bacteriological sample submitted to Department? Yes X No If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes No					
TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped					
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile					
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded X					
		7 Fiberglass SDR26 Threaded					
Blank casing diameter 5 in. to 77 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface in. weight 200 lbs./ft. Wall thickness or gauge No. 3/16							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) SDR26							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut X 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes							
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 30 ft. to 77 ft. From ft. to ft.							
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From top ft. to 30 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage							
Direction from well? Livestock S = E		How many feet? 80					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS		
		old well					
		65 feet old well					
		4 feet Blue clay					
		12 feet Drill 3 feet gravelly shale Blue					
		5 feet					
		Backing Shale					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Aug 20 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 221 This Water Well Record was completed on (mo/day/yr) Nov 17 1990							
under the business name of Frank Buckle by (signature) Frank Buckle							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							