

WATER WELL RECORD Form WWC-5 KSA 82a-1212

LOCATION OF WATER WELL: County: Butts Fraction: SW 1/4 NE 1/4 Section Number: 16 Township Number: T 24 S Range Number: R 3 EW

Distance and direction from nearest town or city street address of well if located within city? City: Melvin

WATER WELL OWNER: RR#, St. Address, Box #: 106 Locust W hitwater Kansas City, State, ZIP Code: 67154 Board of Agriculture, Division of Water Resources Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing section box with X in NE quadrant]

DEPTH OF COMPLETED WELL: 66 ft. ELEVATION: 66 ft.

Depth(s) Groundwater Encountered: 1. 20 ft. 2. 30 ft. 3. 15 ft.

WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr Aug 21 1984

Pump test data: Well water was 30 ft. after 1 hours pumping 15 gpm

Est. Yield: 15 gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: 8 in. to ft. and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes X No

TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass SDR 26 Threaded

Blank casing diameter: 6 in. to 30 ft. Dia in. to ft. Dia in. to ft.

Casing height above land surface: 18 in. weight lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SDR 26 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 40 ft. From 50 ft. to 60 ft.

GRAVEL PACK INTERVALS: From 10 ft. to 66 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 20 ft. to 10 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? How many feet? 75 E

LITHOLOGIC LOG

FROM	TO	LITHOLOGIC LOG
0	4	topsoil
4	20	Blue Clay
20	30	fine Blue Sand
30	40	Blue Shale
40	50	Blue Clay
50	60	fine Blue Sand
60	66	Blue Shale

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) Aug 21 1984 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 221 This Water Well Record was completed on (mo/day/yr) Jan 6 1984 under the business name of Frank Budd by (signature) Frank Budd

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.