

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Butler		SE ¼ SW ¼ NE ¼	30	T 24 S	R 4 E/V
Distance and direction from nearest town or city street address of well if located within city? ~1000'W of K196 & ~950'E of NW Adams Rd., Potwin					
2 WATER WELL OWNER: MRP Properties Company, LLC RR#, St. Address, Box # : PO Box 696000 City, State, ZIP Code : San Antonio, TX 76269-6000		Board of Agriculture, Division of Water Resources Application Number:			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 51 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was NA ft. after hours pumping gpm			
		Est. Yield NA gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9.75 in. to 38.5 ft., and 5.75 in. to 52 ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes.....No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped			
1 Steel 3 RMP (SR)		5 Wrought iron 8 Concrete tile			
2 PVC 4 ABS		6 Asbestos-Cement 9 Other (specify below) Welded			
Blank casing diameter 6 in. to 38 ft. Dia 2 in. to 41 ft. Dia in. to ft.		7 Fiberglass Threaded. <input checked="" type="checkbox"/>			
Casing height above land surface 2.34 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40					
TYPE OF SCREEN OR PERFORATION MATERIAL		10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR)		11 Other (specify)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Wire wrapped 9 Drilled holes		10 Other (specify)			
2 Louvered shutter 4 Key punched 7 Torch cut					
SCREEN-PERFORATED INTERVALS: From 41 ft. to 51 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 39 ft. to 52 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0.5 ft. to 39 ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		12 Fertilizer storage 16 Other (specify below)			
2 Sewer lines 5 Cess pool 8 Sewage lagoon 13 Insecticide storage					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard		How many feet?			
Direction from well?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Clay, silty, Dark Brown			
1	10.6	Clay, Med. Brown			
10.6	15	Clay, some silt, Lt. Brown			
15	20.8	Clay, silty, Grayish Tan			
20.8	23	Sand (f), silty, Gray			
23	29.9	Limestone, Lt. Gray			
29.9	31	Shale, Gray and Tan			
31	35.8	Shale, Green			
35.8	42	Shale, Brick Red			
42	48.4	Limestone,			
48.4	50.1	Shale, Tan			
50.1	55	Shale, Gray			
					SCIMW-19(D), Abovegrade
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/7/2009 and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 8/28/2009					
under the business name of GeoCore, Inc. by (signature) <i>Joe Kef</i>					