

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Butler		SE ¼ SW ¼ NE ¼		30		T 24 S		R 4 E/W	
Distance and direction from nearest town or city street address of well if located within city? ~1000'W of K196 & ~950'E of NW Adams Rd., Potwin									
2 WATER WELL OWNER: MRP Properties Company, LLC PO Box 696000 San Antonio, TX 76269-6000 RR#, St. Address, Box # : City, State, ZIP Code :									
Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:			4 DEPTH OF COMPLETED WELL 30 ft ELEVATION:						
			Depth(s) Groundwater Encountered 1. ft 2. ft 3. ft						
			WELL'S STATIC WATER LEVEL ft below land surface measured on mo/day/yr						
			Pump test data: Well water was NA ft after hours pumping gpm						
			Est. Yield NA gpm: Well water was ft after hours pumping gpm						
			Bore Hole Diameter 5.75 in. to 31 ft. and in. to ft.						
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring Was a chemical/bacteriological sample submitted to Department? Yes.....No ☒ ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No ☒									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. ☒									
Blank casing diameter 2 in. to 20 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 2.43 in., weight lbs./ft. Wall thickness or gauge No. Sch. 40									
TYPE OF SCREEN OR PERFORATION MATERIAL									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 20 ft to 30 ft. From ft to ft.									
GRAVEL PACK INTERVALS: From 18 ft to 31 ft. From ft to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout intervals: From 0.5 ft to 18 ft. From ft to ft. From ft to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 1 Clay, silty, Dark Brown									
1 10.6 Clay, Med. Brown with black mottling									
10.6 15 Clay, some silt, Lt. Brown									
15 20.8 Clay, silty, Grayish Tan									
20.8 23 Sand (f), silty, Gray									
23 29.9 Limestone, Lt. Gray									
29.9 31 Shale, Gray and Tan									
SCIMW-20(S) , Abovegrade									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/6/2009 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 8/28/2009 under the business name of GeoCore, Inc. by (signature) <i>Dan Roll</i>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

EW

SEC.

¼

¼

¼