


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1] LOCALITY: WATER WELL: Fraction: SE SW 1/4 NW 1/4 SW 1/4 Section Number: 29 Township Number: T 24 S Range Number: R 4 EW
 County: Butler

Distance and direction from nearest town or city street address of well if located within city?
 1/4 south of Potwin

2] WATER WELL OWNER: Total Petroleum, Inc.
 RR#, St. Address, Box #: P.O. Box 500 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Denver, CO 80201 Application Number:

3] LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4] DEPTH OF COMPLETED WELL: 68 ft. ELEVATION: 1349.1
 Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL: 31.49 ft. below land surface measured on mo/day/yr 11/17
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield: 20+ gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter: 7.7/8 in. to 50 ft., and 12 1/4 in. to 6 3/4-68 ft.
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5] TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued 8" Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded 4"
 Blank casing diameter: 4 in. to 68 ft., Dia 8 in. to 68 ft., Dia in. to ft.
 Casing height above land surface: 2.3 ft. in., weight sched. 40 lbs./ft. Wall thickness or gauge No. .060

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 54 ft. to 68 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From X 51.5 ft. to XX 68 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6] GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 45-59.5
 Grout Intervals: From 0 ft. to 46 ft., From 46 ft. to 46 ft., From 46 ft. to 50.5 ft., From 50.5 ft. to 0-45 ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? at well site How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
		See attached log			

7] CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/17/88 and this record is true to the best of my knowledge and belief. Kansas
 Water Well Contractor's License No. KWWCL 334 This Water Well Record was completed on (mo/day/yr) 1/19/89
 under the business name of Ewbank, Inc. by (signature) Wade Ewbank

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.