


WATER WELL: Fraction SW 1/4 NW 1/4 SW 1/4 Section Number 29 Township Number T 24 S Range Number R 4 B/W
 County: Butler

Distance and direction from nearest town or city street address of well if located within city?

1/4 south of Potwin

WATER WELL OWNER: Total Petroleum, Inc.
 RR#, St. Address, Box #: P.O. Box 500 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Denver, CO 80201 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: DEPTH OF COMPLETED WELL 45 ft. ELEVATION: 1350.08



Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 31.18 ft. below land surface measured on mo/day/yr 11/14/88
 Pump test data: Well water was . ft. after . hours pumping gpm
 Est. Yield 0.75 gpm: Well water was . ft. after . hours pumping gpm
 Bore Hole Diameter 7 7/8 in. to 45 ft. and . in. to . ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes. No. X; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes No

TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded X
 Blank casing diameter 4 in. to 45 ft. Dia . in. to . ft. Dia . in. to . ft.
 Casing height above land surface 1.74 ft. in., weight sched. 40 lbs./ft. Wall thickness or gauge No. 0.060

TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 30 ft. to 45 ft. From . ft. to . ft.
 GRAVEL PACK INTERVALS: From 27 ft. to 45 ft. From . ft. to . ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 24 ft. From 24 ft. to 27 ft. From . ft. to . ft.

What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? at well site How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		see attached log			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/14/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL 334 This Water Well Record was completed on (mo/day/yr) 1/19/89 under the business name of Ewbank, Inc. by (signature) Ewbank