


1 LOCATION OF WATER WELL: County: Butler Fraction: SE 1/4 NW 1/4 NE 1/4 Section Number: 27 Township Number: T 24 S Range Number: R 4 E/W

Distance and direction from nearest town or city street address of well if located within city? 212 N Sturges

2 WATER WELL OWNER: Ron Brown 212 N Sturges P.O. Box 295  
RR#, St. Address, Box # :  
City, State, ZIP Code : Potwin Kan 67603 Board of Agriculture, Division of Water Resources  
Application Number: 67123

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:   
4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION:  
Depth(s) Groundwater Encountered 1. 70 ft. 2. . ft. 3. . ft.  
WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr  
Pump test data: Well water was . ft. after . hours pumping . gpm  
Est. Yield 40 gpm. Well water was . ft. after . hours pumping . gpm  
Bore Hole Diameter: 8 1/2 in. to . ft. and . in. to . ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes . No X; If yes, mo/day/yr sample was submitted  
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped .  
2 PVC 4 ABS 7 Fiberglass . Welded .  
Blank casing diameter . 5 in. to 7 1/2 in. Dia . in. to . ft., Dia . in. to . ft.  
Casing height above land surface . 18 in., weight 160 lbs./ft. Wall thickness or gauge No. 1214  
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 PVC 10 Asbestos-cement  
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) .  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) .  
SCREEN-PERFORATED INTERVALS: From 7 1/2 ft. to 140 ft., From . ft. to . ft.  
From . ft. to . ft., From . ft. to . ft.  
GRAVEL PACK INTERVALS: From . ft. to . ft., From . ft. to . ft.  
From . ft. to . ft., From . ft. to . ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other .  
Grout Intervals: From 0 ft. to 20 ft., From . ft. to . ft., From . ft. to . ft.  
What is the nearest source of possible contamination:  
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage  
Direction from well? E How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	Soil			
6	18	Clay			
18	140	Shale + Lime			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/30/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 251 This Water Well Record was completed on (mo/day/yr) 11/26/91 under the business name of Winter Well Drill by (signature) Charles Winter