


1 LOCATION OF WATER WELL:	Fraction <i>SE 1/4 SE 1/4 SW 1/4</i>	Section Number <i>34</i>	Township Number <i>T 24 S</i>	Range Number <i>R 5 NW</i>
Distance and direction from nearest town or city street address of well if located within city? <i>Ends on 77 1/4 m W 1/4 EL DORADO KS</i>				
2 WATER WELL OWNER:	<i>Galen L. Morris</i>			
RR#, St. Address, Box #:	<i>RR 4</i>			
City, State, ZIP Code:	<i>EL DORADO, KS 67042</i>			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 				
4 DEPTH OF COMPLETED WELL <i>100'</i> ft. ELEVATION: Depth(s) Groundwater Encountered <i>30-40'</i> ft. 2. <i>95 FT</i> ft. 3. ft.				
WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter in. to ft., and in. to ft.				
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 0 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well				
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted				
Water Well Disinfected? Yes No <i>X</i>				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile Casing joints: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <i>7 1/2"</i> in. to <i>30'</i> ft. Dia in. to ft., Dia in. to ft.				
Casing height above land surface <i>100'</i> in., weight lbs./ft. Wall thickness or gauge No.				
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) <i>NA</i> 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) <i>NA</i>				
SCREEN-PERFORATED INTERVALS: From <i>NA</i> ft. to <i>NA</i> ft., From ft. to ft. From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft. From ft. to ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <i>100</i> ft. to <i>10</i> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)				
Direction from well? <i>North west</i> - How many feet? <i>100-150 FT</i>				
FROM	TO	LITHOLOGIC LOG	FROM	TO
				PLUGGING INTERVALS <i>RAN 109 FT / 1" Pipe in well - CIRCULATED CEMENT (1) SURFACE - PULLED OUT 1" PIPE - THEN PUMPED 15 SAX CEMENT DOWN 7" CASING - PRESSURE 100 PSI - CEMENT FILL ABOUT 12' FROM SURFACE - USED 68 SAX 60-40 POSONIX 4 SAX GEL FOR 6 90 5% GILSONITE (340 LBS)</i>
			<i>100</i>	<i>10</i>
			<i>10</i>	<i>0</i>
			<i>CEMENT CLAY</i>	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <i>6/16/93</i> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <i>Galen L. Morris</i> This Water Well Record was completed on (mo/day/yr) by (signature) <i>Galen L. Morris</i>
