

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 SE 1/4 NE 1/4	Section Number 28	Township Number T 25 S	Range Number R 1E E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1601 E. 91st N. Wichita, Kansas

WATER WELL OWNER: SCOTT, Greg	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 1601 E. 91st N.	Application Number:
CITY, STATE, ZIP CODE: Wichita, Kansas	

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 67 ft. ELEVATION:
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 20 FT. BELOW LAND SURFACE MEASURED ON 09/15/1997
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter 12 in. to 40 ft. and in. to ft.	
WELL WATER TO BE USED AS:	5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes <input type="checkbox"/> No <input checked="" type="checkbox"/> ; If yes, mo/day/yr sample was submitted	Water Well Disinfected? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued <input checked="" type="checkbox"/> Clamped
1 Steel 3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Welded	
2 PVC 4 ABS	7 Fiberglass	SDR-26	Threaded	
Blank casing Diameter 5 in. to 37 ft., Dia	in. to ft. , Dia	in. to ft. , Dia	in. to ft.	
Casing height above land surface 12 in., weight 2.35 lbs. / ft.		Wall thickness or gauge No. .214		
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	11 other (specify)	
1 Steel 3 Stainless Steel	6 Concrete tile	9 ABS	12 None used (open hole)	
2 Brass 4 Galvanized steel				
SCREEN OR PERFORATION OPENING ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
1 Continuous slot 3 Mill slot	6 Wire wrapped	9 Drilled holes		
2 Louvered shutter 4 Key punched	7 Torch cut	10 Other (specify)		
SCREEN-PERFORATION INTERVALS:	from 37 ft. to 67 ft., From	ft. to	ft.	
	from	ft. to	ft.	
GRAVEL PACK INTERVALS:	from 24 ft. to 67 ft., From	ft. to	ft.	
	from	ft. to	ft.	

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other bentonite hole plug
Grout Intervals: From 4 ft. to 24 ft. From		ft. From	ft. to	ft.
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandon water well
				15 Oil well/Gas well
				16 Other (specify below)
				None Apparent

Direction from well?				How many feet?	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	topsoil			
4	18	clay			
18	30	fine sand			
30	32	clay			
32	48	medium sand			
48	67	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/15/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/16/97 Under the business name of Harp Well & Pump Service, Inc by signature Todd S. Harp
