


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SW 1/4 SE 1/4	SECTION NUMBER 31	TOWNSHIP NUMBER T 25 S	RANGE NUMBER R 1E E/W
---	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
1/2 mile East of Meridian & 500 ft. North of 77th St. N. Valley Center, Kansas

2 WATER WELL OWNER: RR#,ST. ADDRESS,BOX #: CITY, STATE:	VALLEY CENTER, CITY OF PO Box 188 Wichita, Kansas	Board of Agriculture, Division of Water Resource Application Number: 20040203 ZIP CODE: 67147
--	--	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 42 ft. ELEVATION: Depth of groundwater Encountered: _____ ft. WELL'S STATIC WATER LEVEL 12 FT. BELOW LAND SURFACE MEASURED ON 10/29/04 Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm Bore Hole Diameter 12 in. to 42 ft. and _____ in. to _____ ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO
--	---

5 TYPE OF CASING USED: 1. Steel 3. RPM (SR) 2. PVC 4. ABS	5. Wrought Iron 7. Fiberglass 9. Other (Specify below) 6. Asbestos-Cement 8. Concrete tile SDR-26	CASING JOINTS: Glued Threaded Welded Clamped
Blank casing diameter 8 in. to 20 ft., Dia. in. to ft., Dia. in. to ft.	Casing height above land surface: 12 in., Weight: 5.52 lbs. / ft.	Wall thickness or gauge No. .332
TYPE OF SCREEN OR PERFORATION MATERIAL: 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)		
SCREEN - PERFORATION INTERVAL From 20 ft. to 42 ft., From ft. to ft., From ft. to ft.		
GRAVEL PACK INTERVALS: From 20 ft. to 42 ft., From ft. to ft., From ft. to ft.		

6 GROUT MATERIALS: Grout Intervals: From 0 ft. to 20 ft.,	1. Neat cement 2. Cement Grout 3. Bentonite From ft. to ft., From ft. to ft.,	Other bentonite hole plug From ft. to ft.
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well 2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below) 3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage None Apparent		
Direction from well? _____ How many feet? _____		

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	4	topsoil			
4	12	clay			
12	22	sand			
22	25	clay			
25	42	sand			

RECEIVED
NOV 22 2004
BUREAU OF WATER

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 10/29/2004 and this record is true to the best of my knowledge and belief.		
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11/01/2004		
under the business name of Harp Well & Pump Service Inc. by (signature) <i>Jo dd S. Harp</i>		