


1 LOCATION OF WATER WELL: County: Sedgwick Fraction: NW 1/4 NE 1/4 NW 1/4 Section Number: 32 Township Number: T 25S S Range Number: R 1E E/W

Distance and direction from nearest town or city street address of well if located within city?
465 Fiddlers Creek; Valley Center

2 WATER WELL OWNER: Jim Hein
 RR#, St. Address, Box #: 465 Fiddlers Creek
 City, State, ZIP Code: Valley Center, KS
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 138 ft. ELEVATION:
 Depth(s) Groundwater Encountered: 32 ft. 2 32 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 32 ft. below land surface measured on mo/day/yr: 12/13/04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 9 Dewatering 12 Other (Specify below)
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter: 5 in. to 138 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface: 16 in., weight: 160 lbs./ft. Wall thickness or guage No. 26
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement
 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify)
 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 80 ft. to 130 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to 138 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? North How many feet? 20

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|-----|----------------|------|----|--------------------|
| 0 | 2 | topsoil | | | |
| 2 | 26 | clay | | | |
| 26 | 31 | Fine sand | | | |
| 31 | 47 | blue shale | | | |
| 47 | 57 | red shale | | | |
| 57 | 72 | blue shale | | | |
| 72 | 79 | green shale | | | |
| 79 | 138 | blue shale | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/13/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 1011 This Water Well Record was completed on (mo/day/yr) 1/21/05 under the business name of Chase Drilling by (signature) R. Chase