

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

Blank box for application number

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction SW 1/4 NE 1/4 NW 1/4 Section Number 29 Township Number T 25 S Range Number R 1 EW

Distance and direction from nearest town or city street address of well if located within city? 501 KANZA VALLEY CENTER, KS 67147 Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: RR#, St. Address, Box #: 501 KANZA City, State, ZIP Code: VALLEY CENTER, KS 67147

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-section grid with 'X' in the NW section] 4 DEPTH OF COMPLETED WELL: 60 ft. Depth(s) Groundwater Encountered: (1) 22 ft. WELL'S STATIC WATER LEVEL: 22 ft. below land surface measured on mo/day/yr. Pump test data: Well water was 25 gpm after 5 hours pumping. Est. Yield: 25 gpm. Well water was after hours pumping. WELL WATER TO BE USED AS: 5 Public water supply, 8 Air conditioning, 11 Injection well, 12 Other (Specify below) 1 Domestic, 3 Feedlot, 6 Oil field water supply, 9 Dewatering, 10 Monitoring well, 2 Irrigation, 4 Industrial, 7 Domestic (lawn & garden). Was a chemical/bacteriological sample submitted to Department? No. Water well disinfected? No.

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below). CASING JOINTS: Glued, Clamped, Welded, Threaded. Blank casing diameter: 5 in. to 40 ft., Diameter. Casing height above land surface: 12 in., Weight: 240 lbs./ft. Wall thickness or gauge No. 160 PLF. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 Torch cut, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole). SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Guazed wrapped, 6 Wire wrapped, 7 Saw Cut, 8 Other (specify), 9 Drilled holes, 10 Other (specify), 11 None (open hole). SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. GRAVEL PACK INTERVALS: From 20 ft. to 60 ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 3 ft. to 20 ft. What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below). Direction from well? SE. How many feet? 80.

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include lithologic logs: TOP SOIL, CLAY, FINE SAND, CLAY, MEDIUM SAND, SHALE.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-14-06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 740. This Water Well Record was completed on (mo/day/year) 2-10-06 under the business name of WENINGER DRILLING INC by (signature).

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.