	WATER WELL RECOR	RD Forn	n WW0	C-5 KS	SA 82a-121	2		
1 LOCATION OF WATER WELL:				N NUMBER	TOWNSHIP NUMBER		RANGE NUMBER	
Sedgwick	SE 1/4 SE 1/4	SW 1/4	4	31	T 25	S	R 1E	E/W
Distance and direction from nearest town or city street address of well if located within city? 1/2 mile East of Meridian, 1/8 mile North of 77th St. N. Valley Center, Kansas								
2 WATER WELL OWNER: MATZKE, Wayne								
	Stone Ridge					Board of Agric	culture, Division of Wa	ter Resource
CITY, STATE: Vall	ey Center, Kansas		ZIP	CODE:		Application Num	ber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WELL:	45	ft.		ELEVATION:			
N De	epth of groundwater Encountered:		ft.			ft.		ft.
	'ELL'S STATIC WATER LEVEL	15 FT.	BELOW	LAND SU	RFACE MEASU	RED ON mo/d	lay/yr: 10/29/	07
NWNE	Pump test data:	Well water w			ft. after		of pumping @	gpm
W E E	Est. Yield: gpm Bore Hole Diameter 12 in	Well water w	as to 45	ft.	ft. after		of pumping @	gpm
	/ELL WATER TO BE USED AS:	1.	10 43	ı.	and	in.	to na 11. Inject	ft. ion well
	5. Dewatering							
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well								
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO								
5 TYPE OF CASING USED:			0.046				\succeq	Threaded
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Office (Specify Below) 5. Wrough								
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-20								
Blank casing diameter 5	in. to 30 ft.,	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No214								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)								
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)								en noie)
2. Louvered shutter 4. Key j	punched 6. Wire wrapped	(8. Saw	cut	10. Oth	er (specify)		
SCREEN - PERFORATION INTERVAL	From 30 ft.	to	45	ft.,	From	ft.	to	ft.
	From ft.	to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS:	From 24 ft.	to	45	ft.,	From	ft.	to	ft.
	From ft.	to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout				Bentonite		Other bent	onite hole plu	g
						ft.		
What is the nearest source of possible contamination: 1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well						as well		
2. Sewer lines 5. Cess	0.0	n 11. F	uel stora	age	14. Aband	on water well	16. Other (spe	cify below)
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage								
Direction from well? West					How ma	any feet? 40 i		
From To	LITHOLOGIC LOG	F	rom	То		LITHOLO	OGIC LOG	
0 4 topsoil								
4 15 clay 15 45 medium coa	rea cand		-					
13 43 menum coa	i se sauu							
	<u> </u>							
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and								
was completed on (mo/day/year) 10/29/2007 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 11-2-2007								
under the business name of Harp Well and Pump Service by (signature) Todd S. Hourp								