WATE	R WELI	RECORD	Form WW	C-5	Division of Water	er Resources; App. No.		
1 LOC	ATION C	WATER WELL;	Fraction	. 1	Section Number		Range Number	
Coun	ty:	ed guid	n or city street address of	NW 1/4	$-\lambda 2$	T 25(S)	R EW	
			n or city street address of	well if		Systems (decimal degr	rees, min. of 4 digits)	
located within city? 1800 E 98th N Latitude:								
2 337.47	TED STEE	· •	, , ,		Longitude:			
2 WA'	St Addr	L OWNER: Ray	, I've mengy					
City	, St. Addre , State, ZII	ess, Box # : / Sob	£ 98 ot	, l	Datum:			
		Vac	ley Center, K		Data Collection			
1	ATE WE	LL'S 4 DEPTH OF (COMPLETED WELL.	<i>f.0.0</i>	ft			
1	ATION	1 D 1 () C	1 . 5 . 1 . 1		0 (0)	6 (2)	0	
l .	WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered (1)							
SEC	WELL'S STATIC WATER LEVEL							
	Est. Yieldgpm: Well water was							
w NV	WELL WATER TO BE USED AS: 5 Public water supply 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 12 Other (Specify below)							
W	2 (rrigation) 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well							
SV	Was a chemical/bacteriological sample submitted to Department? Yes No .X; If yes, mo/day/yrs							
	Sample was submitted							
s								
5 TYPI	E OF CAS	ING USED: 5 Wro	ought Iron 8 Co	ncrete tile	CASIN	G JOINTS: Glued	Clamped	
	Steel	3 RMP (SR) 6 Ast	pestos-Cement 9 Ot	her (specify	below)	G JOINTS: Glued Welded		
6	DVC	AADS 7 Eib.	aralass		•	Threaded		
Blank casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.								
Casing I	neight abov	e land surface	2 in., Weight	60	lbs./ft. Wall thi	ckness or guage No.	2.b	
TYPE C	F SCREE	N OR PERFORATION I		•				
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify)								
2 Brass 4 Galvanized Steal 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)								
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw cut 10 Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
CPAVEL DACK INTERVALS. From 21 ft to 177 ft From ft to ft								
GRAVEL PACK INTERVALS: From 24 ft. to /02 ft., From ft. to ft. From ft. to ft.								
6 GRO	UT MATI	ERIAL: 1 Neat cemen	t 2 Cement grout (3)	Bentonite	4 Other			
Grout In			to ft., From .		ft. to	ft., From	ft. toft.	
1		source of possible conta						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide storage 16 Other (specify								
	Sewer line			11 Fuel st	•	bandoned water well	below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/gas well Direction from well?								
			OGTAT OG					
FROM	TO	LITHOL	OGIC LOG	FROM	ТО	PLUGGING INT	ERVALS	
02	2	Sop Soul						
Δ	17	Chair						
17	3/	June	Shole					
3/	100	Blue	Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged								
under my jurisdiction and was completed on (mo/day/year) . S								
Kansas Water Well Contractor's License No Le. 14 This Water Well Record was completed on (mo/day/year) 2 2 2								
under the business name of have Williams by (signature) for the business name of								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PLINT clearly. Please fill in blanks, underline or carele the correct answers. Send top								
three copi	es to Kansas	Department of Health and Env	rironment, Bureau of Water, Ge	ology Section	, 1000 SW Jackson St.,	Suite 420, Topeka, Kansas	66612-1367. Telephone	
785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us a								
http://www.kdheks.gov/waterwell/index.html.								