

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NE 1/4 SE 1/4 NW 1/4	SECTION NUMBER 30	TOWNSHIP NUMBER T 25 S	RANGE NUMBER R 1E E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
3/8 mile South of 93rd St. N. & 1/2 mile East of Meridian (4 logs on 1 permit) Valley Center, Kansas

2 WATER WELL OWNER: VALLEY CENTER, CITY OF	Board of Agriculture, Division of Water Resource		
RR#, ST. ADDRESS, BOX #: P.O. Box 188	ZIP CODE: 67147	Application Number: 20100061	
CITY, STATE: Valley Center, Kansas			

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 40 ft. ELEVATION: _____ ft. Depth of groundwater Encountered: _____ ft. ft. ft. WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON 3/2/10 mo/day/yr. Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm Bore Hole Diameter 12 in. to 40 ft. and _____ in. to _____ ft. WELL WATER TO BE USED AS: 1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below) Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted Was Water Well Disinfected? YES NO
--	--

5 TYPE OF CASING USED:	1. Steel	3. RPM (SR)	5. Wrought Iron	7. Fiberglass	9. Other (Specify below)	CASING JOINTS:	Glued	Threaded	
	2. PVC	4. ABS	6. Asbestos-Cement	8. Concrete tile	SCH-40		Welded	Clamped	
Blank casing diameter	8 in.	to	20 ft.,	Dia. in.	to	ft.,	Dia. in.	to	ft.
Casing height above land surface:	12 in.,	Weight:	5.52 lbs. / ft.	Wall thickness or gauge No.	.332				
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1. Steel	3. Stainless Steel	5. Fiberglass	7. PVC	9. ABS	11. Other (specify)				
2. Brass	4. Galvanized	6. Concrete Tile	8. RMP (SR)	10. Asbestos-Cement	12. None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:									
1. Continuous slot	3. Mill slot	5. Gauzed wrapped	7. Torch cut	9. Drilled holes	11. None (open hole)				
2. Louvered shutter	4. Key punched	6. Wire wrapped	8. Saw cut	10. Other (specify)					
SCREEN - PERFORATION INTERVAL									
From	20 ft.	to	40 ft.,	From	ft.	to	ft.		
From	ft.	to	ft.,	From	ft.	to	ft.		
GRAVEL PACK INTERVALS:									
From	20 ft.	to	40 ft.,	From	ft.	to	ft.		
From	ft.	to	ft.,	From	ft.	to	ft.		

6 GROUT MATERIALS:	1. Neat cement	2. Cement Grout	3. Bentonite	Other bentonite hole plug							
Grout Intervals: From	0 ft.	to	20 ft.,	From	ft.	to	ft.,	From	ft.	to	ft.
What is the nearest source of possible contamination:											
1. Septic tank	4. Lateral lines	7. Pit privy	10. Livestock pens	13. Insecticide storage	15. Oil well/Gas well						
2. Sewer lines	5. Cess Pool	8. Sewage lagoon	11. Fuel storage	14. Abandon water well	16. Other (specify below)						
3. Watertight sewer line	6. Seepage pit	9. Feed yard	12. Fertilizer storage	None Apparent							
Direction from well?										How many feet?	

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	12	clay			
12	22	fine sand			
22	40	medium sand			

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/2/2010 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236	This water well record was completed on (mo/day/year) 3/8/2010
under the business name of Harp Well and Pump Service	by (signature) Todd S. Harp