WATER WELL RECORD Form WWC-5 KSA 82a-1212										
111	LOCATION OF WATER WELL: FRACTION				1	SECTION NUMBER TOWNSHIP NUMBER			RANGE NUMBER	
Sedgwick		NW 1/4	NW 1/4	NW 1/4	<u> </u>	14	Т	25 S	R 1E	E/W
Distance and direction fro 10910 N. Hills	-									
10910 N. Hillside Wichita, Kansas 2 WATER WELL OWNER: WILLS, Randy										
RR#,ST. ADDRESS		10 N. Hillside						Board of Agr	iculture, Division of W	ater Resource
CITY,	STATE: Wic	hita, Kansas			ZIF	CODE: 6	7147	Application Nur	mber:	
3 LOCATE WELL'S LO	OCATION 4	DEPTH OF COMPI	LETED WELL:	60	ft.		ELEVATION:			
WITH AN "X" IN SEC	De	epth of groundwater	Encountered:		ft.			ft.		ft.
	w	ELL'S STATIC WA	TER LEVEL	15 FT.	BELOV	W LAND SU	RFACE MEAS	SURED ON mo/	day/yr: 7/27/	10
NW	NE		•	Well water w			ft. after		s of pumping @	gpm
W Mile		Est. Yield:	gpm 12 in.	Well water w	_	Λ 4	ft. after		s of pumping @	gpm
∑ w		Bore Hole Diameter /ELL WATER TO BI			to 6	U ft.	and	in.	to ina 11. Injec	ft. tion well
sw	1_			ıblic water s	upply <	7. Lawn a	nd garden or	9. Dewater	12. Other (Sp	
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well										
S		Was a chemical/bacteri ubmitted	iological sample subn	nitted to Depar	tment?	YES Was W	/ater Well Dis	•	what mo/day/yr wa	•
5 TYPE OF CAS			7.5%		9 01			ASING JOINTS:	\succeq	Threaded
1. Steel 3. RPM (SR) Welded Clamped										
2. PVC	> 4. ABS	6. Asbestos		ncrete tile	SDI	(-20				
Blank casing diameter	er 5		35 ft., I	Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above		12 _{in.,}	Weig	ght: 2.3	5 lb	s. / ft.	Wall	thickness or gau	ge No214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)										
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)										
, , , , , , , , , , , , , , , , , , , ,										
SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)										oen hole)
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)										·
SCREEN - PERFORA		From	35 ft.	to	60	ft.,	From			
SCREEN - PERFOR	ATION INTERVAL	From	ft.	to	00	ft.,	From	ft.	to	ft.
GRAVEI PA	CK INTERVALS:	From	24 ft.	to	60	ft.,	From	ft. ft.	to to	ft.
O TOTAL ET A	OK INTERVALO.	From	ft.	to	v	ft.,	From			ft.
6 GROUT MATER	IAI S: 4 None						110111	ft. Other hen	to	ft.
GROUT MATERIALS: 1. Neat cement 2. Cement Grout 3. Bentonite Other bentonite had a grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft.								•	g ft.	
What is the nearest source of possible contamination:										
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage								15. Oil well/G		
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)										
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage Direction from well? Northeast How								many feet? 100) ft. nlus	
From To		LITHOLOGIC	LOG	IF	rom	To	110111		OGIC LOG	
0 4	topsoil									
4 15	clay									
15 50 50 60	fine sand									
50 00	inie sami									
					-					

									·····	
7 Contractor's or	Landowner's Certif	fication: This water	well was 1. cons	structed	2. rec	onstructed	or 3.	plugged	under my jurisdiction	on and
was completed on	(mo/day/year)	7/27/2010	and this	record is tru	e to the	best of my	knowledge and	d belief.		
Kansas Water Wel	Contractor's Licer	nse No. 236	This	water well re	cord was	s completed	on (mo/day/ye	ear) 7/29	0/2010	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harb										