KSA 82a-1212 WATER WELL RECORD Form WWC-5 1 LOCATION OF WATER WELL: FRACTION SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE SE 1/4 NW1/4 30 Т 25 S 1E E/W R Distance and direction from nearest town or city street address of well if located within city? 3/8 mile So. of 93rd No., 1/2 mile East of Meridian (7 plugs on 1 permit) Valley Center, Kansas VALLEY CENTER, CITY OF WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: P.O. Box 188 ZIP CODE: 67147 20100060 Valley Center, Kansas CITY, STATE: Application Number: 4 DEPTH OF COMPAGE WELL 40 ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. N WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 7/16/10 Pump test data: Well water was ft. after map MW NE Est. Yield: gpm Well water was ft. after hours of pumping @ gpm Ξ 12 to 40 Bore Hole Diameter and ft WELL WATER TOOK USED AS: 11. Injection well 9. Dewatering SE 7. Lawn and garden only 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) Was Water Well Disinfected? YES 5 TYPE OF CASING USED: 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped 6. Asbestos-Cement 8. Concrete tile 4. ABS 2. PVC 8 Blank casing diameter Dia. ft... Dia in. to ft.. to in. to ft. Casing height and surface: 36 Weight: lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 11. Other (specify) N/A 3. Stainless Steel 7. PVC 9. ABS Fiberglass 1. Steel Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole) 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 8. Saw cut 10. Other (specify) N/A 2 Louvered shutter 6. Wire wrapped 4. Key punched SCREEN - PERFORATION INTERVAL ft. ft.. From to From ft. ft. to From ft., From ft. GRAVEL PACK INTERVALS: to From ft.. From to ft. ft. From to ft., From to ft. 6 **GROUT MATERIALS:** Other bentonite hole plug 2 Cement Grout 1. Neat cement 3. Bentonite 3 23 From Grout Intervals: From ft. ft., ft. ft. to From What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 1. Septic tank 4. Lateral lines 16. Other (specify below) 11. Fuel storage 8. Sewage lagoon 14. Abandon water well 5. Cess Pool 2. Sewer lines None Apparent 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line How many feet? Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From To From To 0 3 compacted topsoil 23 bentonite hole plug 3 23 chlorinated well gravel 40 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed 3. < plugged under my jurisdiction and or 7/16/2010 and this record is true to the best of my knowledge and belief. was completed on (mo/day/year) Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 7/19/2010 Todd S. Harb under the business name of Harp Well and Pump Service by (signature)