		Water Well Record	Form WWC-5	KSA 82a-1212			
LOCATION OF WATER WELL;	FRACTION		_	Section Number	Township Number	Range Number	
Sedgwick NE 1/4		SW 1/4 SV	V 1/4	1	_T 25 _S	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?							
	Valley Center						
	anhourst, Dal	.e					
RR#, ST. ADRESS, BOX #: 317 Dover CITY, STATE, ZIP CODE: Valley Center, Kansas							
	The state of the s		~ -	<u> </u>	Application Numb	er:	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		WEST WELL	35		EVATION:	_	
	Depth(s) groundw		1	ft.	2 ft.	3 ft.	
	WELL'S STATIC W				URFACE MEASURED ON mo/day/yr	05/22/1998	
	Pump tes		ater was	ft.	after hours pur	* O	
9[]	Est. Yield	C.	ater was	ft.	after hours pur		
eji w	Bore Hole Diameter (C**	to Dock!! to	ft.	and in.	to ft.	
	1 Domestic		Public water		0	Injection well	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	2 Irrigation		Oil field wa Lawn and g	** *	9 Dewatering 12 0 10 Monitoring well	Other (Specify below)	
	•	·			8		
S S	Was a chemical/bact submitted	eriological sample su	bmitted to D	-		no/day/yr sample was	
5 TYPE OF CASING USED:	Submitted				ater Well Disinfected? Yes		
1 Steel 3 RMP (SR)		5 Wrought iron 6 Asbestos-Cemen		Concrete tile Other (Specify		Glued Clamped	
2 PVC 4 ABS		7 Fiberglass	, ,	Other (Specify	*	Welded Fhreaded x	
	t 4	Ü					
Blank casing Diameter 1 1/4 Casing height above land surface 3	in. to in.,	ft., Dia	in.	to	ft., Dia in.	to ft.	
TYPE OF SCREEN OR PERFORA	weight	lbs. / ft. Wall thickness or gauge No. 7 PVC 10 Asbestos-cement					
,					DMD (CD)		
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS			11 other (specify) N/A 12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous slot 3 Mill slot		6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key pt		• •			/A		
CORPEN REPEORATION INTERVALC						•	
SCREEN-FERFORATION INTERV		ft.		ft., Froi		ft.	
from		ft.		ft., From		ft.	
GRAVEL PACK INTERVALS: from			ft. to ft., F			ft.	
6 GROUT MATERIAL: 1 Neat	from 2.0	ft. Cement grout		ft., Fro itonite	m ft. to 4 Other bentonite	holo plug	
Grout Intervals: From 0	ft. to 6				_	and the same of th	
What is the nearest source of possible contamination:		it. From	ft. From ft. to 10 Livestock		ft. From 6	ft. to 25 ft.	
1 Septic tank 4 Lateral lines					A Tribundon Water Well		
2 Sewer lines 5 Cess pool					el storage 15 Oil well/Gas well retilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit			9 Feedyard 13 Insecticide storage			other (speerly below)	
Direction from well? South How many feet? 12							
FROM TO LITHOLOGIC LOG			FROM	ТО	PLUGGING INTI	ERVALS	
			0	6	cement grout		
			6	25	bentonite hole plu	ıg	
			25	35	chlorinated sand a	and gravel	
					,		
					MANAGEMENT LITTLE STORY		
				<u> </u>			
			_			1.00	
			_				
	THE STATE OF THE S		<u> </u>				
			<u> </u>				
	en and a second of the second	-81	<u> </u>				
7 CONTRACTOR'S OR LANDOWN	ER'S CERTIFICATION: T	his water well was	(1) construc	cted, (2) recon	structed, or (3) plugged und	er my jurisdiction and	
was completed on (molday/yea	m 05/22/1	998	and this	record is true	to the best of my knowledge	e and belief. Kansas	
Water Well Contractor's Licens	e No.6	This Wate	r Well Reco	ord was compl	leted on 05/26	5/98	
Water Well Contractor's License 10.6							
Under the business name of				by	(signature) Jodd x	S. Harp	