

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick	FRACTION NW 1/4 NE 1/4 SE 1/4	SECTION NUMBER 31	TOWNSHIP NUMBER T 25 S	RANGE NUMBER R 1E E/W
---	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?
1210 E. Northridge Valley Center, Kansas

2 WATER WELL OWNER: COLBY, Tomas	Board of Agriculture, Division of Water Resource
RR#, ST. ADDRESS, BOX #: 1210 E. Northridge	Application Number:
CITY, STATE: Valley Center, Kansas	ZIP CODE:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 46 ft. ELEVATION:
	Depth of groundwater Encountered: _____ ft.
	WELL'S STATIC WATER LEVEL: 16 FT. BELOW LAND SURFACE MEASURED ON 3/17/16
	Pump test data: Well water was _____ ft. after _____ hours of pumping @ _____ gpm
	Est. Yield: _____ gpm Well water was _____ ft. after _____ hours of pumping @ _____ gpm
Bore Hole Diameter: 12 in. to 46 ft. and _____ in. to _____ ft.	WELL WATER TO BE USED AS:
1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well	12. Other (Specify below)
2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well	
Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted _____	Was Water Well Disinfected? YES NO

5 TYPE OF CASING USED:	CASING JOINTS: Glued Threaded Welded Clamped
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)	SDR-26
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile	
Blank casing diameter: 5 in. to 36 ft., Dia. _____ in. to _____ ft.	
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214	
TYPE OF SCREEN OR PERFORATION MATERIAL:	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:	
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)	
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)	
SCREEN - PERFORATION INTERVAL From 36 ft. to 46 ft., From _____ ft. to _____ ft.	
GRAVEL PACK INTERVALS: From 24 ft. to 46 ft., From _____ ft. to _____ ft.	

6 GROUT MATERIALS:	Other bentonite hole plug
1. Neat cement 2. Cement Grout 3. Bentonite	
Grout Intervals: From 4 ft. to 24 ft., From _____ ft. to _____ ft.	
What is the nearest source of possible contamination:	
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well	
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)	
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage	
Direction from well? North	How many feet? 40 ft. plus

From	To	LITHOLOGIC LOG	From	To	LITHOLOGIC LOG
0	3	topsoil			
3	14	clay			
14	30	fine sand			
30	36	clay			
36	45	medium sand			
45	46	grey shale			

7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 3/17/16 and this record is true to the best of my knowledge and belief.	
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 3/21/16	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp	