WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER Sedgwick NE 1/4  $\mathbf{s}\mathbf{w}$ 1/4 SE 31 Т 25 s R 1E Ε/W 1/4 Distance and direction from nearest town or city street address of well if located within city? Valley Center, Kansas 510 S. Stoneridge ROBINSON, Robert WATER WELL OWNER: Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 510 S. Stoneridge Valley Center, Kansas CITY, STATE: ZIP CODE Application Number: 4 DEPTH OF COMPLETED WELL: 47 ft. **ELEVATION:** LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX 8/7/17 ft. ft. ft. Depth of groundwater Encountered: WELL'S STATIC WATER LEVEL FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: Pump test data: Well water was ft. after hours of pumping @ gpm NW NE Est. Yield: apm Well water was ft. after hours of pumping @ apm Ē 12 and Bore Hole Diameter ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 5. Public water supply 7. Lawn and garden only  $\mathbf{x}^{\mathsf{E}}$ SW 1. Domestic 3. Feedlot 12. Other (Specify below) 10. Monitoring well 2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO (YES) Was Water Well Disinfected? NO 5 TYPE OF CASING USED: CASING JOINTS: Glued Threaded 9. Other (Specify below) 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 4. ABS 2. PVC to 37 ft.. Dia. ft.. Dia. ft. Blank casing diameter in. in. to in to 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. Casing height above land surface: .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify) 1. Steel 8. RMP (SR) 12. None used (open hole) 6. Concrete Tile 10. Asbestos-Cement 2. Brass 4. Galvanized SCREEN OR PERFORATION OPENINGS ARE: 9. Drilled holes 11. None (open hole) 7. Torch cut 1. Continuous slot 3. Mill slot 5. Gauzed wrapped 2. Louvered shutter 6. Wire wrapped 8. Saw cut 10. Other (specify) 4. Key punched SCREEN - PERFORATION INTERVAL From to ft., From to ft. From ft. to ft., From ft ft to 24 GRAVEL PACK INTERVALS: ft. to ft., From From to ft. ft to From From ft.. ft to ft. Other **GROUT MATERIALS:** 2. Cement Grout 3. Bentonite bentonite hole plug 1. Neat cement Grout Intervals: 4 ft. 24 ft From From ft. to ft., From ft. What is the nearest source of possible contamination: 10. Livestock pens 15. Oil well/Gas well 7. Pit privy 13. Insecticide storage 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 2. Sewer lines 5. Cess Pool 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line How many feet? 40 ft. plus Direction from well? From LITHOLOGIC LOG From Τо LITHOLOGIC LOG То 0 tonsoil 10 3 clay 10 25 fine sand 25 47 medium sand Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and 8/7/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/9/17 Todd S. Harb by (signature) under the business name of Harp Well and Pump Service