WATER WELL RECORD Form WWC-5 KSA 82a-1212 1 LOCATION OF WATER WELL: SECTION NUMBER TOWNSHIP NUMBER RANGE NUMBER SE SE NE 9 25 Sedgwick Т 1E 1/4 1/4 1/4 S R E/W Distance and direction from nearest town or city street address of well if located within city? Valley Center, Kansas 11565 N. Hydraulic WATER WELL OWNER: SALMERON, Luis Board of Agriculture, Division of Water Resource RR#,ST. ADDRESS,BOX #: 11565 N. Hydraulic ZIP CODE: 67147 Valley Center, Kansas CITY, STATE: Application Number: 4 DEPTH OF COMPLETED WELL: 70 ELEVATION: LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth of groundwater Encountered: ft. ft. ft. WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr: 10/20/17 Pump test data: Well water was ft. after hours of pumping @ apm NW NE Est. Yield: gpm Well water was ft. after hours of pumping @ apm 12 to 70 Ē Bore Hole Diameter and ft. WELL WATER TO BE USED AS: 11. Injection well 9. Dewatering 7. Lawn and garden only SW SE 1. Domestic 3. Feedlot 5. Public water supply 12. Other (Specify below) 10. Monitoring well 6. Oil field water supply 8. Air conditioning 4. Industrial ; If yes, what mo/day/yr was sample Was a chemical/bacteriological sample submitted to Department? (NO) (YES Was Water Well Disinfected? 5 TYPE OF CASING USED 9. Other (Specify below) CASING JOINTS: Glued Threaded 7. Fiberglass 5. Wrought Iron 3. RPM (SR) 1. Steel Welded Clamped SDR-26 8. Concrete tile 6. Asbestos-Cement 2. PVC 4. ABS 5 40 Blank casing diameter ft., Dia. in. ft.. Dia in. ft. to 12 Weight: 2.35 lbs. / ft. Wall thickness or gauge No. Casing height above land surface: in.. .214 TYPE OF SCREEN OR PERFORATION MATERIAL: 7. PVC 9. AB\$ 11. Other (specify) 3. Stainless Steel 5. Fiberglass 1. Steel 8. RMP (SR) 12. None used (open hole) 2. Brass 4 Galvanized 6. Concrete Tile 10. Asbestos-Cement SCREEN OR PERFORATION OPENINGS ARE: 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole) 1 Continuous slot 8. Saw cut 10. Other (specify) 6. Wire wrapped 2. Louvered shutter 4. Key punched SCREEN - PERFORATION INTERVAL 40 ft., From From to ft. ft. ft. From to ft., From ft. ft. 24 GRAVEL PACK INTERVALS: to 70 ft.. From ft From to ft. ft From to ft. From ft. to Other bentonite hole plug 6 GROUT MATERIALS: 2 Cement Grout 3 Bentonite 1. Neat cement 4 Grout Intervals: ft. 24 From ft.. From to From ft., What is the nearest source of possible contamination: 10. Livestock pens 7. Pit privy 13. Insecticide storage 15. Oil well/Gas well 4. Lateral lines 1. Septic tank 16. Other (specify below) 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 5. Cess Pool 2 Sewer lines 12. Fertilizer storage 9. Feed yard 6. Seepage pit 3. Watertight sewer line West How many feet? 100 ft. plus Direction from well? LITHOLOGIC LOG LITHOLOGIC LOG From Τо From To 3 0 topsoil 18 3 clav very fine sand 18 32 medium sand 32 48 48 70 grey shale

Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. under my jurisdiction and 10/20/17 was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 10/23/17

under the business name of Harp Well and Pump Service

by (signature)

Todd S. Harp