	WATER WE	LL RECORD	Form W\	NC-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL:	FRACTION			TION NUMBER	ł	IP NUMBER		NUMBER
Sedgwick	SW 1/4	NE 1/4 N	E 1/4	30	<u> </u>	25 S	R 1.	E E/W
Distance and direction from nearest town or o	•							
	illey Center, Kai IIG, Tony	nsas						
	11 N. Seneca					Board of Agri	culture, Division of	Water Resource
	lley Center, Kan	isas	Z	IP CODE: 6	7147	Application Num	nber:	
	DEPTH OF COMPL		116 ft.		ELEVATION:	***		
WITH AN "X" IN SECTION BOX:	Depth of groundwater I		f	t,		ft.		ft.
	WELL'S STATIC WAT				JRFACE MEAS	URED ON mo/o	day/yr: 6/1	8/19
NWNE			water was		ft. after		of pumping @	gpm
	Est. Yield:	•	water was		ft. after	hours	of pumping @	gpm
W William F	Bore Hole Diameter	12 in.	to	116 ft.	and	in.	to	ft.
	WELL WATER TO BE	USED AS:	_			9. Dewateri	9	ection well
SW · · · SE·····					and garden on	עצו 10. Monitorir		Specify below)
s	-	ndustrial 6. Oil flel plogical sample submitted	ld water suppl	y 8. AIRCOI YES	NO		what mo/day/yr	was sample
3	submitted	sogical cample casmice	No Doparimona		Water Well Disir	nfected?	YES	NO
5 TYPE OF CASING USED:	5. Wrought li	ron 7. Fibergl	ass 9. 0	Other (Specify	/ below) CA	SING JOINTS:	Glued	Threaded
1. Steel 3. RPM	(SR)	_	S.L.	R-26			Welded	Clamped
2. PVC 4. ABS	6. Asbestos-		ite tile	11 20				_
Blank casing diameter 5		0 ft., Dia.	in.	to	ft.,	Dia.	in. to	ft.
Casing height above land surface:	12 _{in.,}	Weight:	2.35	lbs. / ft.	Wall t	hickness or gaug	ge No214	1
TYPE OF SCREEN OR PERFORATI 1. Steel 3. Stainless Steel		7. PVC		ABS	11 C	other (specify)		
1. Steel 3. Stainless Steel 2. Brass 4. Galvanized	 5. Fiberglass 6. Concrete Til 			Asbestos-Cei		lone used (open	hole)	
		o. 1411 (O	10.1		12.11	iono adda (opon		
SCREEN OR PERFORATION OPENI 1. Continuous slot 3. Mill		auzed wrapped	7 T .	orch cut	9 Dri	lled holes	11. None (open hole)
		, ,					(
2. Louvered shutter 4. Key	punched 6. W	ire wrapped		aw cut	10. 00	her (specify)		
SCREEN - PERFORATION INTERVA	L From	40 ft.	to 116	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS	: From	24 ft.	to 116	ft.,	From	ft.	to	ft.
	From	ft.	to	ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Ne	at cement	2. Cement Grout		3. Bentonite	•	Other bent	onite hole p	lug
Grout Intervals: From	ft. to	ft., Fro	m ft	. to	ft.,	From 4	ft. to	24 ft.
What is the nearest source of possible 1. Septic tank 4. Late		Pit privy	10. Livesto	ck pens	13. Insec	ticide storage	15. Oil well/	Gas well
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well						16. Other (s	pecify below)	
		Feed yard	12. Fertilize	er storage				
Direction from well? East	hade bu			•	How n	nany feet? 52 1	ft. plus	
From To	LITHOLOGIC	LOG	From	То	2	LITHOLO	GIC LOG	
0 3 topsoil								
3 20 clay				<u> </u>				
20 26 fine sand 26 116 grev shale				1				
26 116 grey shale				†				
				-				
	——————————————————————————————————————			<u> </u>				
				1				
				<u> </u>				
					I			
Contractor's or Landowner's Cer		vell was 1. constru	cted 2. r	econstructe	d or 3.	plugged	under my jurisdi	ction and
was completed on (mo/day/year)	6/18/19	and this rec	ord is true to th	e best of my	knowledge and	l belief.		
Kansas Water Well Contractor's Lic	ense No. 236	This water	er well record w	as completed	d on (mo/day/ye	ear) 6/2	21/19	
under the business name of Har	p Well and Pum	p Service	by (s	signature)	T	odd S	. Hari	b