


LOCATION OF WATER WELL: County: Sedgwick Fraction: SW 1/4 SW 1/4 NE 1/4 Section Number: 12 Township Number: T 25 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city? 6 No Kechi. KS 1/2 E 1/2 NO.

WATER WELL OWNER: Jeff Lyle  
 RR#, St. Address, Box #: Wichita KS  
 City, State, ZIP Code: Wichita KS

Board of Agriculture, Division of Water Resources  
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 20 ft.  
 Depth(s) Groundwater Encountered 1. 20 ft. 2. 20 ft. 3. 20 ft.  
 WELL'S STATIC WATER LEVEL: 20 ft. below land surface measured on mo/day/yr 12-24-81  
 Pump test data: Well water was 45 ft. after 1/2 hours pumping 10 gpm  
 Est. Yield 1-3 gpm: Well water was 45 ft. after 1/2 hours pumping 10 gpm  
 Bore Hole Diameter: 10 in. to 65 ft., and 10 in. to 65 ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) TEST HOLE  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted 12-24-81  
 Water Well Disinfected? Yes X No X

TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) NONE 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped X  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X  
 7 Fiberglass Threaded X

Blank casing diameter 10 in. to 65 ft., Dia 10 in. to 65 ft., Dia 10 in. to 65 ft.  
 Casing height above land surface 10 in., weight 10 lbs./ft. Wall thickness or gauge No. 10

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel NONE 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) TEST HOLE  
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify) TEST HOLE

SCREEN-PERFORATED INTERVALS: From 0 ft. to 20 ft., From 20 ft. to 65 ft.  
 GRAVEL PACK INTERVALS: From 0 ft. to 20 ft., From 20 ft. to 65 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 65 ft.

What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			Method of Plugging Gravel - to 12 ft from surface. Cement Grout - 12 ft to 2 ft from surface. Top soil - top 2 ft.
2	14	gray clay			
14	65	gray shale & clay			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-24-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 1-7-82 under the business name of Wenger Drilling by (signature) Joanille J...  
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.