


LOCATION OF WATER WELL: County: Sedgwick Fraction: NE 1/4 NE 1/4 SW 1/4 Section Number: 15 Township Number: T 25 S Range Number: R 1 E/W

Distance and direction from nearest town or city street address of well if located within city? 1 1/2 N. of Ks Coliseum on N. Hydraulic E side

WELL OWNER: Ken Shafflin
 RR#, J. Address, Box #: 2000 Coliseum Circle
 City, State, ZIP Code: Wichita, KS
 Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



DEPTH OF COMPLETED WELL: 80 ft. ELEVATION: 56 ft.

Depth(s) Groundwater Encountered 1. 12 ft. 2. 40 ft. 3. 56 ft.

WELL'S STATIC WATER LEVEL: 12 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 10 ft. after 10 hours pumping 10 gpm

Est. Yield 10 gpm: Well water was 10 ft. after 10 hours pumping 10 gpm

Bore Hole Diameter: 10 in. to 10 in. and 10 in. to 10 in.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes ✓ No ✓; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes ✓ No ✓

TYPE OF BLANK CASING USED:

5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped

1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded

2 PVC 4 ABS 7 Fiberglass Threaded

Blank casing diameter 5 in. to 5 ft., Dia. 5 in. to 5 ft., Dia. 5 in. to 5 ft.

Casing height above land surface +12 in., weight #200 lbs./ft. Wall thickness or gauge No. 200

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement

2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)

1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes

2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 80 ft. to 60 ft., From 80 ft. to 60 ft., From 80 ft. to 60 ft.

GRAVEL PACK INTERVALS: From 80 ft. to 15 ft., From 80 ft. to 15 ft., From 80 ft. to 15 ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout Intervals: From 15 ft. to 3 ft., From 15 ft. to 3 ft., From 15 ft. to 3 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well

2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well

3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)

Direction from well? How many feet? +100'

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
80	56	Gray shale			
56	13	Sandy Brown clay			
13	4	Brown clay			
4	0	earth			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) April 14, 1982 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 424 This Water Well Record was completed on (mo/day/yr) May 17th 1982

under the business name of Reisner Well Drilling by (signature) Jerry Reisner
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.