


LOCATION OF WATER WELL: County: Sedgwick Fraction: SW 1/4 SW 1/4 SW 1/4 Section Number: 18 Township Number: T 25 S Range Number: R 10 E/W

Distance and direction from nearest town or city street address of well if located within city?  
2 No Valley Center Ks.  
 WATER WELL OWNER: Haug Const  
 RR#, St. Address, Box #: EX 36  
 City, State, ZIP Code: Sedgwick KS 67135  
 Board of Agriculture, Division of Water Resources  
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  
  
 DEPTH OF COMPLETED WELL: 73 ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. 14 ft. 2. 40 ft. 3. 15 ft.  
 WELL'S STATIC WATER LEVEL 14 ft. below land surface measured on 9-25-81  
 Pump test data: Well water was 40 ft. after 1/2 hours pumping 15 gpm  
 Est. Yield 15-25 gpm: Well water was 40 ft. after 1/2 hours pumping 15 gpm  
 Bore Hole Diameter: 11 in. to 73 ft., and 73 in. to 73 ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic  3 Feedlot  6 Oil field water supply  9 Dewatering  12 Other (Specify below)  
 2 Irrigation  4 Industrial  7 Lawn and garden only  10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes  No   
 If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes  No

TYPE OF BLANK CASING USED:  
 1 Steel  3 RMP (SR)  5 Wrought iron  8 Concrete tile   
 2 PVC  4 ABS  6 Asbestos-Cement  9 Other (specify below)   
 7 Fiberglass   
 CASING JOINTS: Glued  Clamped   
 Welded   
 Threaded   
 Blank casing diameter 5 in. to 21 ft., Dia 21 in. to 73 ft., Dia 73 in. to 73 ft.  
 Casing height above land surface 12 in., weight 1.59 lbs./ft. Wall thickness or gauge No. SOR-26

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel  3 Stainless steel  5 Fiberglass  8 RMP (SR)  10 Asbestos-cement   
 2 Brass  4 Galvanized steel  6 Concrete tile  9 ABS  11 Other (specify)   
 12 None used (open hole)   
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot  3 Mill slot  5 Gauzed wrapped  8 Saw cut  11 None (open hole)   
 2 Louvered shutter  4 Key punched  6 Wire wrapped  9 Drilled holes   
 7 Torch cut  10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 21 ft. to 73 ft., From 73 ft. to 73 ft., From 73 ft. to 73 ft.  
 GRAVEL PACK INTERVALS: From 13 ft. to 73 ft., From 73 ft. to 73 ft., From 73 ft. to 73 ft.

GROUT MATERIAL: 1 Neat cement  2 Cement grout  3 Bentonite  4 Other   
 Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 73 ft., From 73 ft. to 73 ft., From 73 ft. to 73 ft.  
 What is the nearest source of possible contamination:  
 1 Septic tank  4 Lateral lines  7 Pit privy  10 Livestock pens  14 Abandoned water well  
 2 Sewer lines  5 Cess pool  8 Sewage lagoon  11 Fuel storage  15 Oil well/Gas well  
 3 Watertight sewer lines  6 Seepage pit  9 Feedyard  12 Fertilizer storage  16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? N-NW How many feet? 125

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	TOP SOIL			
2	10	RED CLAY			
10	17	FINE SAND			
17	30	RED CLAY			
30	73	GRAY SHALE & CLAY GRAY			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-25-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 10-1-81 under the business name of Wagner's Drilling by (signature) [Signature]  
 INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.